

Real-Time Water Quality Deployment Report

Rattling Brook Network

August 10, 2021 to September 21, 2021



Government of Newfoundland & Labrador
Department of Environment and Climate Change
Water Resources Management Division
St. John's, NL, A1B 4J6 Canada

General

- Department of Environment and Climate Change staff monitor the real-time web pages consistently.
- Hydrometric data included in this report is provisional and used only for illustrative purposes. Corrected and finalized data may be retrieved from the Water Survey of Canada website (https://wateroffice.ec.gc.ca/index_e.html)*.

Maintenance and Calibration of Instrument

- As part of the Quality Assurance and Quality Control protocol (QAQC), an assessment of the reliability of data recorded by an instrument is made at the beginning and end of the deployment period. The procedure is based on the approach used by the United States Geological Survey.
 - Upon deployment, a QA/QC Sonde is temporarily deployed *in situ*, adjacent to the Field Sonde. Depending on the degree of difference between each parameter from the Field and QAQC sondes, a qualitative rank is assigned (See Table 1). The possible ranks, from most to least desirable, are: Excellent, Good, Fair, Marginal, and Poor. A grab sample is also taken for additional confirmation of conditions at deployment and to allow for future modelling studies.
 - At the end of a deployment period, a freshly cleaned and calibrated QAQC Sonde is placed *in situ*, adjacent to the Field Sonde. Values are compared between all parameters and differences are ranked for placement in Table 1.


Table 1: Qualitative QAQC Ranking

Station	Date	Action	Comparison Ranking				
			Temperature	pH	Conductivity	Dissolved Oxygen	Turbidity
Rattling Brook Big Pond	August 10	Deployment	Good	Good	Excellent	Good	Marginal
	September 21	Removal	Fair	Good	Good	Good	Excellent
Rattling Brook below Bridge	August 10	Deployment	Fair	Excellent	Excellent	Excellent	Excellent
	September 21	Removal	Excellent	Good	Excellent	Excellent	Excellent
Rattling Brook below Plant Discharge	August 10	Deployment	Excellent	Good	Excellent	Excellent	Excellent
	September 21	Removal	Excellent	Good	Excellent	Good	Excellent

- Data Interpretation

Temperature

Water Temperature is a major factor used to describe water quality. Temperature has major implications on both the ecology and chemistry of a water body, governing processes such as the metabolic rate of aquatic plants and animals and the degree of dissolved oxygen saturation.




Station	Max	Min	Median	Mean
Big Pond	20.79	15.80	18.51	18.38
Below Bridge	24.29	13.74	18.97	18.84
Below Plant Discharge	25.02	12.95	18.44	18.69

- Water temperature peaked in mid-August before slowly declining in September.

*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

pH

pH is used to give an indication of the acidity or basicity of a solution. A pH of 7 denotes a neutral solution while lower values are acidic and higher values are basic. Technically, the pH of a solution indicates the availability of protons to react with molecules dissolved in water. Such reactions can affect how molecules function chemically and metabolically.




Station	Max	Min	Median	Mean
Big Pond	6.66	5.56	6.12	6.15
Below Bridge	6.70	5.79	6.37	6.33
Below Plant Discharge	6.61	5.73	6.35	6.29

- At all stations, pH values showed a downward trend over the deployment period with major drops related to precipitation events. The majority of values were within the site-specific guidelines (5.67-6.56 pH Units).

*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.


Specific Conductivity

Conductivity relates to the ease of passing an electric charge – or resistance – through a solution. Conductivity is highly influenced by the concentration of dissolved ions in solution: distilled water has zero conductivity (infinite resistance) while salty solutions have high conductivity (low resistance). Specific Conductivity is corrected to 25°C to allow comparison across variable temperatures.



*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Rattling Brook Network, Long Harbour, Newfoundland and Labrador



Station	Max	Min	Median	Mean
Big Pond	100.0	63.9	69.6	70.1
Below Bridge	66.8	55.5	59.7	59.5
Below Plant Discharge	82.4	57.0	62.3	62.4

- Specific conductivity was relatively stable at all stations during this deployment period with few fluctuations due to variations in Stage caused by precipitation. There are increases at Big Pond not related to precipitation. This may be due to wave action from the pond occasionally stirring up sediment around the sonde, increasing the conductivity.

*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.


Dissolved Oxygen

Dissolved oxygen is a metabolic requirement of aquatic plants and animals. The concentration of oxygen in water depends on many factors, especially temperature – the saturation of oxygen in water is inversely proportional to water temperature. Oxygen concentrations also tend to be higher in flowing water compared to still, lake environments. Low oxygen concentrations can give an indication of excessive decomposition of organic matter or oxidation reactions.



*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Rattling Brook Network, Long Harbour, Newfoundland and Labrador




Station	Max	Min	Median	Mean
Big Pond	9.19	6.98	8.55	8.53
Below Bridge	10.22	8.20	9.04	9.06
Below Plant Discharge	10.02	7.68	8.64	8.65

- Trend lines show that in September the cooler water temperatures increases the dissolved oxygen concentrations as cooler water holds more oxygen.
- During this deployment period, all values remained above the minimum CCME Aquatic Guideline for other life stages (6.5 mg/l).

*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Turbidity

Turbidity is typically caused by fine suspended solids such as silt, clay, or organic material. Consistently high levels of turbidity tend to block sunlight penetration into a waterbody, discouraging plant growth. High turbidity can also damage the delicate respiratory organs of aquatic animals and cover spawning areas.



Station	Max	Min	Median	Mean
Big Pond	215.4	0.0	0.0	2.8
Below Bridge	273.1	0.0	0.0	1.6
Below Plant Discharge	157.5	0.0	0.1	1.5

- Most turbidity peaks are associated with precipitation events and are of short duration.

*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Appendix

