



# Real-Time Water Quality Deployment Report

## Rattling Brook Network

February 17, 2022 to March 22, 2022



Government of Newfoundland & Labrador  
Department of Environment and Climate Change  
Water Resources Management Division  
St. John's, NL, A1B 4J6 Canada

**General**

- Department of Environment and Climate Change staff monitor the real-time web pages consistently.
- Hydrometric data included in this report is provisional and used only for illustrative purposes. Corrected and finalized data may be retrieved from the Water Survey of Canada website ([https://wateroffice.ec.gc.ca/index\\_e.html](https://wateroffice.ec.gc.ca/index_e.html))\*.

**Maintenance and Calibration of Instrument**

- As part of the Quality Assurance and Quality Control protocol (QAQC), an assessment of the reliability of data recorded by an instrument is made at the beginning and end of the deployment period. The procedure is based on the approach used by the United States Geological Survey.
  - Upon deployment, a QA/QC Sonde is temporarily deployed *in situ*, adjacent to the Field Sonde. Depending on the degree of difference between each parameter from the Field and QAQC sondes, a qualitative rank is assigned (See Table 1). The possible ranks, from most to least desirable, are: Excellent, Good, Fair, Marginal, and Poor. A grab sample is also taken for additional confirmation of conditions at deployment and to allow for future modelling studies.
  - At the end of a deployment period, a freshly cleaned and calibrated QAQC Sonde is placed *in situ*, adjacent to the Field Sonde. Values are compared between all parameters and differences are ranked for placement in Table 1.

Table 1: Qualitative QAQC Ranking





Station	Date	Action	Comparison Ranking				
			Temperature	pH	Conductivity	Dissolved Oxygen	Turbidity
Rattling Brook Big Pond	December 2	Deployment	Excellent	Good	Good	Excellent	Fair
	March 22	Removal	Excellent	Good	Good	Fair	Excellent
Rattling Brook below Bridge	February 17	Deployment	Good	Excellent	Good	Excellent	Excellent
	March 22	Removal	Good	Fair	Good	Excellent	Excellent
Rattling Brook below Plant Discharge	February 17	Deployment	Excellent	Good	Good	Marginal	Excellent
	March 22	Removal	Excellent	Good	Good	Fair	Fair

- During the weekend of January 7<sup>th</sup>, the Vale weather station was compromised during a wind event. As the data is suspect, this report is utilizing weather data from St. John’s West, 78kms NE from Long Harbour.

- Data Interpretation

Temperature

*Water Temperature is a major factor used to describe water quality. Temperature has major implications on both the ecology and chemistry of a water body, governing processes such as the metabolic rate of aquatic plants and animals and the degree of dissolved oxygen saturation.*




Station	Max	Min	Median	Mean
Big Pond	2.39	0.04	1.05	1.03
Below Bridge	4.43	-0.52	0.48	0.60
Below Plant Discharge	5.16	-0.56	0.66	0.89

- Water temperature slowly increased at mid deployment at Below Bridge and Plant Discharge.

\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

## pH

*pH is used to give an indication of the acidity or basicity of a solution. A pH of 7 denotes a neutral solution while lower values are acidic and higher values are basic. Technically, the pH of a solution indicates the availability of protons to react with molecules dissolved in water. Such reactions can affect how molecules function chemically and metabolically.*




Station	Max	Min	Median	Mean
Big Pond	5.21	4.82	5.01	5.02
Below Bridge	7.18	5.56	6.39	6.33
Below Plant Discharge	6.51	6.03	6.29	6.30

- pH values were generally consistent with the majority of values within the site-specific guidelines (5.67-6.56 pH Units) with the exception of Big Pond which showed low pH throughout, likely from sensor drift.

\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.


### Specific Conductivity

Conductivity relates to the ease of passing an electric charge – or resistance – through a solution. Conductivity is highly influenced by the concentration of dissolved ions in solution: distilled water has zero conductivity (infinite resistance) while salty solutions have high conductivity (low resistance). Specific Conductivity is corrected to 25°C to allow comparison across variable temperatures.



\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Rattling Brook Network, Long Harbour, Newfoundland and Labrador




Station	Max	Min	Median	Mean
Big Pond	64.3	49.8	56.6	56.8
Below Bridge	157.8	20.8	52.4	53.2
Below Plant Discharge	108.5	48.5	53.5	55.9

- Specific conductivity was relatively stable at all stations. Occasional peaks at both Below Bridge and Plant Discharge stations throughout the deployment were likely due to runoff from higher than normal temperatures and precipitation events.

\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.


## Dissolved Oxygen

*Dissolved oxygen is a metabolic requirement of aquatic plants and animals. The concentration of oxygen in water depends on many factors, especially temperature – the saturation of oxygen in water is inversely proportional to water temperature. Oxygen concentrations also tend to be higher in flowing water compared to still, lake environments. Low oxygen concentrations can give an indication of excessive decomposition of organic matter or oxidation reactions.*



\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

Rattling Brook Network, Long Harbour, Newfoundland and Labrador



Station	Max	Min	Median	Mean
Big Pond	14.44	12.27	12.97	12.97
Below Bridge	14.75	12.27	14.14	14.07
Below Plant Discharge	14.05	11.64	13.44	13.36


- Dissolved oxygen concentrations plateaued. Abnormal warm periods throughout the deployment caused DO fluctuations for a short period of time at Rattling Brook below Discharge and Below Bridge.
- During this deployment all measurements were found to be above the CCME dissolved oxygen guideline of 9.5 mg/L for the protection of early life stage cold-water biota.

\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.



## Turbidity

*Turbidity is typically caused by fine suspended solids such as silt, clay, or organic material. Consistently high levels of turbidity tend to block sunlight penetration into a waterbody, discouraging plant growth. High turbidity can also damage the delicate respiratory organs of aquatic animals and cover spawning areas.*



Station	Max	Min	Median	Mean
Big Pond	155.4	0.6	1.4	2.5
Below Bridge	88.4	0.0	0.0	0.9
Below Plant Discharge	97.9	0.0	2.0	4.8

- Turbidity levels were low during this deployment period with variation only observed during high flow and melting events. Plant Discharge sonde was encased in ice during the beginning of the deployment.

\*All hydrometric data is provisional and is subject to correction. Please consult Water survey of Canada for finalized data and interpretation.

### Appendix

