

# Government of Newfoundland and Labrador Department of Environment and Conservation Water Resources Management Division

#### PERMIT TO OPERATE

Pursuant to the Water Resources Act, SNL 2002 cW-4.01, specifically Section(s) 38

Date:

**APRIL 23, 2015** 

File No: <u>844.097.16</u> Permit No: <u>OP-W-7854-2015</u>

Permit Holder:

City of St. John's

P.O. Box 908

St. John's NL A1C 5M2

Attention:

**Andrew Niblock** 

Re:

St. John's - Permit to Operate - Windsor Lake Water Treatment Plant

For the operation of a:

Class IV Water Treatment Plant

- This Permit is valid until Thursday, April 23, 2020 or until there is a change in the classification of the water treatment or water
- This Permit does not release the Permit Holder from the obligation to obtain appropriate approvals from other concerned municipal, provincial and federal agencies.
- This Permit is subject to the terms and conditions indicated in Appendices A and B (attached).

distribution system as applicable, or as may be determined by this Department.

Failure to comply with the terms and conditions will render this Permit null and void, place the Permit Holder and their agent(s) in violation
of the Water Resources Act and make the Permit Holder responsible for taking any remedial measures as may be prescribed by this
Department.



MINISTER

### GOVERNMENT OF NEWFOUNDLAND AND LABRADOR Department of Environment and Conservation

File No: <u>844.097.16</u> Permit No: <u>OP-W-7854-2015</u>

## APPENDIX A Terms and Conditions for Permit

#### **DW-General**

- 1. The Owner shall operate and maintain a drinking water system which shall include the following:
  - a, a surface water supply from Windsor Lake;
  - b. a 1440 mm raw water screened intake and travelling screen;
  - c. an underground raw water storage reservoir with a volume of 1820 m<sup>3</sup>;
  - d. treatment capabilities for:
  - pre-treatment pH adjustment (carbon dioxide)
  - pre-treatment pH adjustment (lime)
  - pre-chlorination (chlorine gas)
  - five primary and three secondary microfiltration membrane units
  - a UV disinfection system (three units)
  - a sodium hypochlorite and citric acid cleaning system; a sodium hydroxide and sodium bisulphite neutralizing system
  - · post chlorination systems (chlorine gas)
  - e. process control, instrumentation and data management systems:
  - f. a filter backwash engineered wetland treatment system;
  - g. a treated water storage reservoir with a volume of 20,000 m <sup>3</sup>;
- 2. The Owner shall operate the drinking water system in accordance with any applicable regulations, policy, guidelines, and this approval, or as may be directed by the Department of Environment and Conservation. Water supplied to the consumer shall satisfy the requirements of the latest version of the Guidelines for Drinking Water Quality in Newfoundland and Labrador, the Newfoundland and Labrador Microbiological Standards, and the Newfoundland and Labrador Disinfection Standards.
- The Owner shall ensure that all chemicals and materials used in the operation of the drinking water system that come into contact with water within the system shall meet all applicable standards set by both the American Water Works Association (AWWA) and the American National Standards Institute (ANSI) safety criteria standards NSF/60 or NSF/61.
- 4. The most current chemical and material product registration documentation from a testing institution accredited by either the Standards Council of Canada or by ANSI shall be available at all times for each chemical and material used in the operation of the drinking water system that comes into contact with water within the system.
- The Owner shall practice a multi-barrier approach to protect the quality of drinking water from the source to the end of the water distribution system within the Owner's jurisdiction.
- 6. The Owner shall endeavour to take all necessary steps to ensure protection of the water supply source from contamination. The operators must establish and maintain a regular inspection routine to monitor activities within the water supply area.
- The Owner shall ensure a copy of this permit is kept in a conspicuous place so that it is available for reference by all persons responsible for all or part of the operation of the drinking water system.
- 8. The Owner shall maintain a sufficient inventory of spare parts for the most critical components of the drinking water system in order to keep downtime and disruptions to the system to a minimum. In particular, an adequate inventory of spare parts for the disinfection system must be maintained to ensure continuous disinfection.
- 9. The Owner shall develop and promote a water conservation program to reduce water demand on the drinking water system.
- 10. The Owner shall take preventative or corrective action as directed by this Department to address any identified deficiencies that may pose a risk to public health or the environment.

#### DW-Disinfection

- 11. A summary of emergency procedures shall be posted outside the chlorine room.
- 12. The Owner shall monitor and document chlorine consumption on a daily basis.
- 13. Disinfection facilities should be kept at an adequate temperature to ensure the integrity of disinfection chemicals is not compromised.
- 14. The Owner should periodically check UV disinfection systems for proper operation including calibration to ensure UV transmission has not fallen below certified levels, cleaning UV lamps of any fouling, and replacing UV lamps once life expectancy has been exceeded or as recommended by the manufacturer.

#### **DW-Water Treatment**

- 15. The Owner shall operate the water treatment facility to treat water at a rate not exceeding the maximum flow rate of 100,000 m<sup>3</sup>/d or 20,000 m<sup>3</sup>/d per primary membrane unit.
- 16. The Owner shall only use the following chemicals in the treatment process and cleaning systems, unless otherwise approved by this Department:
  - a. carbon dioxide
  - b. hydrated lime
  - c. chlorine gas
  - d. sodium hypochlorite
  - e, citric acid
  - f. sodium hydroxide
  - g. sodium bisulphite
- 17. The residuals effluent discharge from the filter backwash engineered wetland treatment system to Windsor Lake and the discharge to sanitary sewer must be in compliance with *The Environmental Control Water and Sewage Regulations*, 2003 and the Canadian Water Quality Guidelines for the Protection of Aquatic Life, as applicable.
- 18. Sludge must be removed from the residuals treatment lagoon as warranted to maintain adequate functioning, and transported and disposed in a manner that is acceptable to the Department of Environment and Conservation.
- 19. The Owner shall ensure that access to the treatment plant is maintained year-round.
- 20. The Owner shall ensure that the treatment facility is reasonably secure from all unauthorized intrusions and shall maintain adequate security defences such as plant surveillance, adequate fencing and gates, and other measures as may be deemed necessary to prevent vandalism and unauthorized entry.
- 21. The Owner shall ensure the use of proper housekeeping techniques to keep the water treatment facility clean. All functioning components and housing structures shall be kept in good repair and well maintained.
- 22. The Owner shall ensure that all backflow prevention devices that are in use in the water treatment facility to prevent the backflow of contaminants into the potable water system are installed, maintained and tested on a regular basis by a certified installer and tester.
- 23. The Owner shall monitor and document filter rates, filter backwash rates, chemical dilutions, chemical feed rates and air flow rates as applicable.

#### **DW-Operators**

- 24. There shall be a person or persons designated by the Owner with the overall authority for the operation and maintenance of the water treatment facility the Operator in Direct Responsible Charge.
- 25. Sufficient staffing of Operators must be provided to carry out daily operation and maintenance activities on the drinking water system to ensure reliable operation of the system.
- 26. The Operator(s) in Direct Responsible Charge of the water treatment facility is required to have Class IV Water Treatment Operator Certification status. Other non Direct Responsible Charge Operators are required to have Class II Water Treatment Operator Certification status. These required levels of certification must be achieved at the earliest possible opportunity, if not already achieved, not to exceed 5 years for Operator in Direct Responsible Charge and 4 years for non Direct Responsible Charge Operators from the date of issue of this Permit. Certification must be achieved in accordance with the Operator education and experience requirements of the Policy for Newfoundland and Labrador Water and Wastewater Operator Certification Program. All Operators shall be permitted to certify to one level above that of the water treatment facility they operate.
- 27. Operators must receive a minimum of 24 hours of related training per year. The Owner shall ensure that Operators participate in training opportunities as they arise in order to meet this requirement.
- 28. Contractors who do work on the drinking water system on behalf of the Owner shall do so under the supervision of the Operator in Direct Responsible Charge and be trained in the particular aspect of the operation and maintenance that they have been contracted to do.

#### DW-Monitoring/Records/Reports

- 29. The Owner shall notify the Department of Environment and Conservation prior to implementing significant changes to any process that may adversely affect the quality and/or quantity of the finished water.
- 30. The Owner shall establish a maintenance and operation program that includes the following:
  - The Owner shall develop a Maintenance Assurance Manual (MAM) for their drinking water system as required by the Department of Municipal and Intergovernmental Affairs and this Department.
  - The Owner shall compile and maintain an up to date operations manual that is made available for reference by all persons responsible for all or part of the operation of the drinking water system. The manual must include manufacturer's information on all components of the system including supplier, contact information, specification information, shop drawings, model and serial numbers, date installed or date put into service, length of service, and parts inventory.

- A maintenance schedule must be maintained for task specific items to be completed on a daily, weekly, monthly, and annual basis as may be applicable for the drinking water system.
- An operator's daily log must be kept of items pertaining to the operation and maintenance of the drinking water system. All manual records should include date and time of record and the operator's signature.
- 31. The Owner shall ensure the continuous measurement and recording of:
  - a. Flow rates of water conveyed into individual treatment systems and trains, and the daily volumes of water conveyed into the individual treatment systems.
  - b. Flow rates and daily volumes of water conveyed to the distribution system from each treatment system that has a separate line feeding the distribution system.
- 32. The Owner shall ensure that monitoring of raw and finished water quality (turbidity, pH, temperature, conductivity, UVA/UVT, TOC, chlorine residual, etc.) is undertaken to ensure efficient operation of the water treatment plant.
- 33. The Owner shall maintain complete up to date digital and/or paper as-built drawings of the drinking water system including all major infrastructure components, process flow diagrams (PFDs), and process and instrumentation diagrams (P&IDs).
- 34. The Owner shall ensure that all process control monitoring instruments (including flow measuring devices, pressure sensors, level indicators, and water quality sensors) are maintained, calibrated and replaced in accordance with manufacturer's recommendations.
- 35. The Owner shall immediately report any major problems or malfunctions to the Design Approval Specialist by telephone at (709) 729-2558 or by email at: <a href="waterandsewer@gov.nl.ca">waterandsewer@gov.nl.ca</a>. A written report shall be submitted within seven days to the Department of Environment and Conservation.
- 36. The Owner shall notify consumers at the earliest possible time of malfunctions in the system. The Owner shall also provide advance notice of any planned disruptions for maintenance and repair, upgrading, and flushing, including anticipated duration and any other relevant information. The nature of the circumstance that will result in water quality deterioration must also be communicated to other concerned Departments, as applicable, including the Department of Health and Community Services, Municipal and Intergovernmental Affairs and Service NL.
- 37. The Owner shall establish procedures for receiving and responding to complaints including a reporting system which records what steps were taken to determine the cause of complaint and the corrective measures taken to alleviate the cause and prevent its reoccurrence.
- 38. The Owner shall produce an annual summary report documenting the operation and maintenance of the drinking water system, including as a minimum: daily water production, daily disinfectant residuals, amount of chemicals used, and any issues experienced with the distribution system (heavy rainfall, major leaks, water shortages, algae blooms, beavers in the water source, shutdown of water treatment equipment, etc.).
- 39. Any information requested by Department of Environment and Conservation officials concerning the drinking water system and its operation under this permit, including but not limited to any records required to be kept by this permit, shall be provided to the Department upon request.
- 40. The Owner shall retain all records required by or created in accordance with this approval for a minimum of 5 years from the date of their creation.
- 41. The Owner shall establish long and short term plans for the sustainable operation of the drinking water system. Planning shall incorporate sound fiscal planning for all operational aspects of the system including general maintenance and operation, emergencies, operator training and continuing education, and capital fiscal planning for upgrading, expansion, and replacement.

#### **SCADA**

- 42. Owners with automated Supervisory Control and Data Acquisition (SCADA) systems shall ensure the functionality of all Remote Terminal Units (RTUs)/ Programmable Logic Controllers (PLCs), Master Terminal Units (MTUs), Human Machine Interfaces (HMIs), data historian and trend applications, and communication systems on a daily basis.
- 43. The Owner will keep a backup copy of the SCADA system master database and the HMI. The backup copy may be located on a spare computer or MTU. Data collected by the SCADA system and stored on the MTU must be backed up on a regular basis.
- 44. The computer/MTU containing the SCADA system master database and HMI must be kept in a separate server room that can be locked. The MTU must never be turned off. The computer being used as the MTU shall be cleaned out with compressed air as required.
- 45. Multiple firewalls must be set up on the SCADA system if the Owner is to allow remote access/login to the SCADA system. Passwords used to gain access to different parts of the SCADA system must be changed on a regular basis.
- 46. The computer/MTU housing the SCADA system master database and HMI shall not be networked to the internet other than to perform operations and maintenance on the SCADA system.
- 47. Automatic patches and updates for antivirus software and the computer operating system housing the SCADA system master database and HMI shall be disabled. All updates will be uploaded manually after confirmation from the update source that they will not interfere with

the operation of the SCADA system.

- 48. The Owner shall maintain technical support for the SCADA system, which may include signing a maintenance support agreement with the developer. Updates to the SCADA system shall be installed as provided by the developer.
- 49. Network connections on the SCADA system must be identified and configured to prevent unauthorized access.
- 50. Logging services should be installed onto the SCADA system to track activity such as user log-on, user log-off, etc.

#### **DW-Safety & Emergencies**

- 51. The Owner shall ensure that all self-contained breathing apparatuses (SCBAs) are maintained as per the latest version of the CSA Standard for the Selection, Use and Care of Respirators. Air cylinders which have not been used in any 3-6 month period should be slowly depressurized and recharged with clean, dry, respirable air. The designated system operators must be trained in the use of the breathing apparatus.
- 52. The Owner shall ensure that all eye wash stations are maintained. Portable eye wash stations must be of the 15 minute continuous flush type. Portable stations shall be checked regularly and the solutions replaced as required. Permanent stations should be flushed regularly to ensure an adequate and clean supply of potable water.
- 53. The Owner shall ensure the operation of emergency electrical generation or emergency pumping systems on a regular basis.
- 54. Operation of the drinking water system shall be conducted in accordance with the requirements of the Occupational Health and Safety Act and its regulations for the safety of operators and the general public. All safety requirements (handrails, guards, walkways, gas detectors, alarms, first aid equipment, emergency lighting, etc.) with respect to operation and maintenance of the drinking water system must be met.
- 55. The Owner shall ensure that operators are provided with all the safety clothing, equipment and training required to carry out hazardous activities. Hazards may include contact with sewage, dangerous chemicals and physical hazards such as confined space entry, climbing water storage tanks, buried power hazards, traffic, trenches, heights, etc. Servicing of all safety equipment must be undertaken according to the manufacturer's recommendations.
- 56. The Owner shall provide operators with access to suitable facilities for hand washing and cleaning, and shall provide disinfecting soap and cleaning products and services as may be necessary.
- 57. The Owner shall ensure that all used oil products and other related hazardous wastes generated by the machinery used in the operation of the drinking water system are collected and disposed of in an approved manner. The regional office of Service NL shall be contacted in this regard.
- 58. Emergency warning devices must be checked and exercised on a regular basis to ensure that all systems are operating and functioning properly. In particular, chlorine gas detectors should be tested on a monthly basis and calibrated every 6 months. A log shall be maintained to record the details of emergency warning device maintenance activity.
- 59. Contingency and emergency response plans must be established for all foreseeable what if scenarios such as extensive fire demand, main line breaks, contamination problems, or the SCADA system is hacked. Plans must include notification of all water system users. The Owner shall ensure that adequate equipment and material are available for dealing with emergencies, upset conditions and equipment breakdowns.
- 60. WHMIS and MSDS information will be kept on site where any chemicals are used in the operation of the drinking water system.

### GOVERNMENT OF NEWFOUNDLAND AND LABRADOR Department of Environment and Conservation

File No: <u>844.097.16</u> Permit No: <u>OP-W-7854-2015</u>

### APPENDIX B Special Terms and Conditions for Permit

- 1. The Permit Holder and its agent(s), subcontractor(s), and consultant(s) shall keep all systems and works in good condition and repair and in accordance with all laws, by-laws, directions, rules and regulations of any governmental authority. The Permit Holder or its agent(s), subcontractor(s), or consultant(s) shall immediately notify the Minister if any problem arises which may threaten the structural stability of the systems and works, endanger public safety and/or the environment or adversely affect others and/or any body of water either in or outside the said Project areas. The Permit Holder and its agent(s), subcontractor(s), and consultant(s) shall be responsible for all damages suffered by the Minister and Government resulting from any defect in the systems and works, operational deficiencies/inadequacies, or structural failure.
- 2. The Permit Holder and its agent(s), subcontractor(s), and consultant(s) shall operate the said Project and its systems and works in a manner which does not cause any water related and/or environmental problems, including but not limited to problems of erosion, deposition, flooding, and deterioration of water quality and groundwater depletion, in or outside the said Project areas. The Permit Holder and its agent (s), subcontractor(s), and consultant(s) shall be responsible for any and all damages associated with these problems caused as a result of changes, deficiencies, and inadequacies in the operational procedures by the Permit Holder or its agent(s), subcontractor(s), or consultant(s).
- 3. If the Permit Holder or its agent(s), subcontractor(s), or consultant(s) fails to perform, fulfil, or observe any of the terms and conditions, or provisions of this Permit and/or Ministerial orders and guidelines, as determined by this Department, the Minister may, after providing ten (10) day notice to the Permit Holder, amend, modify, suspend or cancel this Permit in accordance with the Water Resources Act.
- 4. The Permit Holder and its agent(s), subcontractor(s), and consultant(s) indemnify and hold the Minister and Government harmless against any and all liabilities, losses, claims, demands, damages or expenses including legal expenses of any nature whatsoever whether arising in tort, contract, statute, trust or otherwise resulting directly or indirectly from granting this Permit, systems and works in or outside the said Project areas, or any act or omission of the Permit Holder or its agent(s), subcontractor(s), or consultant(s) in or outside the said Project areas, or arising out of a breach or non-performance of any of the terms and conditions, or provisions of this Permit by the Permit Holder or its agent(s), subcontractor(s), or consultant(s).
- 5. This Permit is subject to all provisions of the Water Resources Act and any regulations in effect either at the date of this Permit or hereafter made pursuant thereto or any other relevant legislation enacted by the Province of Newfoundland and Labrador in the future.
- 6. This Permit shall be construed and interpreted in accordance with the laws of the Province of Newfoundland and Labrador.

File No: <u>844.097.16</u> Permit No: <u>OP-W-7854-2015</u>

cc: Mr. Frank Huxter, P. Eng. Director of Municipal Infrastructure & Waste Management Department of Municipal and Intergovernmental Affairs PO Box 8700 St. John's NL A1B 4J6

cc: Mr. Inayat Rehman, P.Eng.
Department of Municipal and Intergovernmental Affairs
Main Floor, West Block, Confederation Bldg.
PO Box 8700
St. John's NL A1B 4J6

cc: Ms. Sharon Williams, Regional Manager Service Newfoundland and Labrador PO Box 8700 St. John's NL A1B 4J6

cc: Ms. Genny DeCoste, P.Tech Design Approval Specialist, Community Water and Wastewater Water Resources Management Division Department of Environment and Conservation PO Box 8700 St. John's NL A1B 4J6

CC: Ms. Deneen Spracklin, P.Eng.
Environmental Engineer, Community Water and Wastewater
Water Resources Management
Environment and Conservation
PO Box 8700
St. John's NL A1B 4J6