



Real-Time Water Quality Deployment Report

Minipi River below Minipi Lake

June 25 to
July 22, 2014



Government of Newfoundland & Labrador
Department of Environment and Conservation
Water Resources Management Division

Contents

General 4

Quality Assurance and Quality Control..... 4

Data Interpretation 6

Minipi River below Minipi Lake..... 6

Conclusions133

Appendix 114

General

- Department of Environment and Conservation staff monitors the real-time web pages regularly.
- This deployment report discusses water quality related events occurring at the station on Minipi River below Minipi Lake.
- On June 25, 2014, a real-time water quality monitoring instrument was deployed at the station on the Minipi River below Minipi Lake. The instrument was deployed for a period of 27 days. The instrument was removed on July 22.

Quality Assurance and Quality Control

- As part of the Quality Assurance and Quality Control protocol (QA/QC), an assessment of the reliability of data recorded by an instrument is made at the beginning and end of the deployment period. The procedure is based on the approach used by the United States Geological Survey.
 - At deployment and removal, a QA/QC Sonde is temporarily deployed along side the Field Sonde. Values for temperature, pH, conductivity, dissolved oxygen and turbidity are compared between the two instruments. Based on the degree of difference between parameters recorded by the Field Sonde and QA/QC Sonde at deployment and at removal, a qualitative statement is made on the data quality (Table 1).

Table 1: Ranking classifications for deployment and removal

	Rank				
Parameter	Excellent	Good	Fair	Marginal	Poor
Temperature (°C)	<=+/-0.2	>+/-0.2 to 0.5	>+/-0.5 to 0.8	>+/-0.8 to 1	<+/-1
pH (unit)	<=+/-0.2	>+/-0.2 to 0.5	>+/-0.5 to 0.8	>+/-0.8 to 1	>+/-1
Sp. Conductance (µS/cm)	<=+/-3	>+/-3 to 10	>+/-10 to 15	>+/-15 to 20	>+/-20
Sp. Conductance > 35 µS/cm (%)	<=+/-3	>+/-3 to 10	>+/-10 to 15	>+/-15 to 20	>+/-20
Dissolved Oxygen (mg/L) (% Sat)	<=+/-0.3	>+/-0.3 to 0.5	>+/-0.5 to 0.8	>+/-0.8 to 1	>+/-1
Turbidity <40 NTU (NTU)	<=+/-2	>+/-2 to 5	>+/-5 to 8	>+/-8 to 10	>+/-10
Turbidity > 40 NTU (%)	<=+/-5	>+/-5 to 10	>+/-10 to 15	>+/-15 to 20	>+/-20

- It should be noted that the temperature sensor on any sonde is the most important. All other parameters can be broken down into three groups: temperature dependant, temperature compensated and temperature independent. Because the temperature sensor is not isolated from the rest of the sonde the entire sonde must be at the same temperature before the sensor will stabilize. The values may take some time to climb to the appropriate reading; if a reading is taken too soon it may not accurately portray the water body.

- Deployment and removal comparison rankings for the station on Minipi River deployed between June 25 and July 22, 2014 is summarized in Table 2.

Table 2: Comparison rankings for Minipi River station June 25 – July 22, 2014.

Station	Date	Action	Comparison Ranking				
			Temperature	pH	Conductivity	Dissolved Oxygen	Turbidity
Minipi River	June 25, 2014	Deployment	Excellent	Excellent	Excellent	Excellent	Fair
	July 22, 2014	Removal	Excellent	Excellent	Excellent	Excellent	Excellent

- At the Minipi River station, all parameters ranked ‘excellent’ at both deployment and removal, except for turbidity. The field sonde read a value of 0.0 NTU, while the QA/QC sonde read a value of 5.1 NTU. This could be due to not giving the QA/QC sonde enough time to stabilize before taking the reading.

Data Interpretation

- The following graphs and discussion illustrate water quality-related events from June 25 to July 22 at the station on Minipi River below Minipi Lake.
- With the exception of water quantity data (stage), all data used in the preparation of the graphs and subsequent discussion below adhere to this stringent QA/QC protocol. Water Survey of Canada is responsible for QA/QC of water quantity data. Corrected data can be obtained upon request.

Minipi River below Minipi Lake

- Water temperature ranged from 11.56 to 19.70°C during this deployment period (Figure 1).
- Water temperature increased slightly throughout the deployment period (Figure 2).





Figure 1: Water temperature at Minipi River below Minipi Lake

**Average Daily Air and Water Temperature: Minipi River below Minipi Lake
June 25 to July 22, 2014**



**Figure 2: Average daily air and water temperatures at Minipi River below Minipi Lake
(weather data collected at Goose Bay)**

- pH ranges between 6.63 and 6.89 pH units throughout the deployment period, with a median value of 6.681 units (Figure 3).
- All values during the deployment are within the CCME Guidelines for the Protection of Aquatic Life (between 6.5 and 9 pH units). pH fluctuates slightly during the day and night.




Figure 3: pH at Minipi River below Minipi Lake

- Specific conductivity ranges from 13.5 to 14.4 $\mu\text{S}/\text{cm}$ (Figure 4).
- Specific conductivity was relatively stable during the deployment period, while stage decreased.




Figure 4: Specific conductivity and stage level at Minipi River below Minipi Lake

- The saturation of dissolved oxygen ranged from 93.9 to 99.6% and a range of 8.75 to 10.49 mg/l was found in the concentration of dissolved oxygen with a median value of 9.30 mg/l (Figure 5).
- All values were above the minimum CCME Guideline for the Protection of Other Life Stage Cold Water Biota of 6.5 mg/l. Most values were below the minimum CCME Guideline for the Protection of Early Life Stage Cold Water Biota value of 9.5 mg/l. The guidelines are indicated in blue on Figure 5.
- Dissolved Oxygen content decreases slightly at the beginning of the deployment period; this is due to the rising water temperature. Dissolved oxygen content fluctuates diurnally, displaying the inverse relationship to water temperature.




Figure 5: Dissolved oxygen and percent saturation at Minipi River below Minipi Lake

- Turbidity values were 0 NTU for the majority of the deployment period. The two large spikes shown on the graph can be attributed to precipitation at that time (Figure 6).




Figure 6: Turbidity and stage level at Minipi River below Minipi Lake

- Stage and precipitation are graphed below to show the relationship between rainfall and water level (Figure 7). Stage decreases throughout the deployment period with varying precipitation records.
- It is important to note the distance between where the precipitation data was collected (~100km to Goose Bay) and the area that drains the Minipi River at this point (~2300km²). There is no significant correlation between precipitation and stage during this time at this station.

**Daily Precipitation and Average Daily Stage Level: Minipi River below Minipi Lake
June 25 to July 22, 2014**




Figure 7: Stage and precipitation at Minipi River below Minipi Lake

Conclusions

- An instrument at the water quality monitoring station on the Minipi River below Minipi Lake was deployed on June 25 and removed on July 22.
- In most cases, weather related events or increase/decreases in water level could be used to explain the fluctuations. Most values recorded were within ranges as suggested by the CCME Guidelines for the Protection of Aquatic Life for pH and dissolved oxygen.
- Temperature increased, while dissolved oxygen decreased slightly. Specific conductivity was relatively stable, and pH was stable. Turbidity was 0 NTU for the majority of the deployment period, with just two large spikes for a short period of time.

Prepared by:
Maria Murphy
Department of Environment and Conservation
Water Resources Management Division
Phone: 709.896.7981
Fax: 709.896.9566

Appendix 1

**Average Daily Air Temperature and Precipitation: Happy Valley-Goose Bay
June 25 to July 22, 2014**

