

# LEAK DETECTION



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Overview

- Theory
- City of St. John's Program
- New Advancements
- Future Projects

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Leak Detection?



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leak Detection?



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Leak Detection

What is Leak Detection?

- The process of identifying and reducing "non revenue" water.
  - Primarily Leaks
  - Illegal Use of Water

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leak Detection

What is Non Revenue Water?

- Unbilled Metered Consumption
- Unbilled Unmetered Consumption
- Unauthorized Consumption
- Customer Meter Inaccuracies
- Leakage within Water Distribution System

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# IWA Water Balance

System Input Volume	Authorised Consumption	Billed Authorised Consumption	Billed Metered Consumption	Revenue Water
			Billed Unmetered Consumption	
		Unbilled Authorised Consumption	Unbilled Metered Consumption	Non Revenue Water
			Unbilled Unmetered Consumption	
	Water Losses	Apparent Losses	Unauthorised Consumption	
			Customer Meter Inaccuracies	
		Real Losses	Leakage on Transmission & Distribution Mains	
			Leakage and Overflows at Reservoirs	
			Leakage on Service Connections up to metering point	

**ST. JOHN'S**

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# IWA Water Balance

In Newfoundland & Labrador the IWA Water Balance is not commonly used due to lack of residential and commercial water meters.

However, we can focus on "Real Losses" within the Water Distribution system.

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION




# Leak Management

Leak Management can be divided into four activities:

1. Asset Management
2. Speed and Quality of Repairs
3. Active Leak Detection
4. Pressure Management

# Leakage Management



**ST. JOHN'S**

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Asset Management

The City of St. John's records information on all water main breaks.


This information is entered into the GIS system. This data is reviewed to determine:

- High concentrations of breaks / leaks
- Areas requiring repairs or replacement
- Selection of Materials

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Asset Management – All WM Breaks



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Asset Management – DI WM Breaks



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Asset Management



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Leak Repairs



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leak Repairs

The volume of water loss due to leakage is a function of flow rate and time – Leak Run Time.

Leak Run Time is comprised of three components:


- Awareness
- Location
- Repair



# Leak Run Time

## Leak Run Time Awareness

**Leak Volume Loss = (A+ L+R) Time x Flow Rate**



**RUN TIME = Awareness\* + Location + Repair**

**ST. JOHN'S**

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leakage Rates

How much water is lost from a water main leak or break?

Answer – It Depends

- Type of Break
- Size of Hole / Opening
- **\*\*Pressure\*\***

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leakage Rates



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leakage Rates

## Typical Water Main Break

- 30 m<sup>3</sup>/hr
- Awareness = 1-2 hours
- Location = 1-2 hours
- Repair = 8 hours
- Total Time = 12 hours
- Volume = 360m<sup>3</sup>



# Leakage Rates



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leakage Rates

## Typical Service Leak

- 3mm Hole in Pipe (1/8")
- Pressure = 70 psi
- Flow = 0.54 m<sup>3</sup>/hr
- Awareness = 3 months
- Location = 1-2 hours
- Repair = 8 hours
- Total Time = 3 months
- Volume = 1166 m<sup>3</sup>

# Leakage Rates

## Summary

- Majority of Water Main breaks are easily and quickly located and repaired.
  - Resulting in short "Leak Run Time"
  - Large Volume of Water lost in Short Period
- Majority of Service Leaks can go undetected for extended periods of time.
  - Resulting in long "Leak Run Time"
  - Large Volume of Water lost in Large Period
- Therefore Leak Detection should be focused on locating leaks that could go undetected.

# Active Leak Control

CSJ's Leak Detection Program is comprised of the following tasks:

- Hydrant Sounding
- Hydrant Leaks versus Main Leaks
- Pin – Point Leak Locations
- Repairs



# Active Leak Control


Leak Locations are determined using Leak Noise Correlator



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION


# Active Leak Control – Correlator Result



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – Correlator Result



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control - Advancements

## District Metered Areas:

- DMA's are defined as discrete areas in which all incoming (and outgoing) water is metered.
- Typically defined by pressure differences caused by various water distribution infrastructure – PRVs, pump stations, water storage reservoirs, etc.
- Flows are monitored to determine possible leaks.



# Active Leak Control - DMAs

## DMA Concept

- Minimum night time flow is calculated, leak detection completed to achieve minimum night flows (typically greater than theoretical calculated result).
- Flow data is monitored daily and minimum night flow is compared to actual flow
- Variance in flows = leak(s) or usage

# Active Leak Control - DMAs

## Ideal DMA Size

- 150-200 Fire Hydrants,
- 2500 Service Connections
- 30 km of Water Mains
- Leak Survey to be Completed in 1-2 days
- Total Leak Run Time of 3-4 days

# Active Leak Control - DMAs



## CSJ DMAs

- 23 Current Zones
- 28+ Proposed Zones
- 12 Zone Water Meters Installed
- 5 Zone Water Meters Installations Planned
- Remote Communications to be Installed in 2010


ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Active Leak Control – DMA Results

Site : KENMOUNT




**ST. JOHN'S**

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Active Leak Control – DMA Results

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Case #1

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Case #2

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Case #3

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Case #4

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION



# Active Leak Control – DMA Case #5

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Case #6

Site : KENMOUNT




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Active Leak Control – DMA Overview

Site : KENMOUNT



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION


# Pressure Management - Future

## Theory of Pressure Management

- During periods of low demand water pressure is reduced below normal setting.
- Lower water pressure will result in reduced leakage and reduced water main breaks
- Typically pressure management is completed during off-peak hours – night time.



# Pressure Management - Concept



ST. JOHN'S


DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Pressure Management - Concept

## Two Basic Types of Pressure Management

- Time of Day
  - Pressure Setting Changed for different times of the Day
- Flow Modulation
  - Pressure Varies with Flow
  - Higher Flow = Higher Pressure
  - Lower Flow = Lower Pressure


# Pressure Management – Time of Day



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION


# Pressure Management – Flow Mod.



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Pressure Management - Equipment




ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION




# Pressure Management – CSJ Example



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Pressure Management – CSJ Example



ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Pressure Management - Savings

## Example of Flow Rates

	3mm (1/8") Hole		4.8mm (3/16") Hole		6.5mm (1/4") Hole	
Pressure	Flow	Volume	Flow	Volume	Flow	Volume
120 psi	0.71m <sup>3</sup> /hr	6195 m <sup>3</sup>	1.59m <sup>3</sup> /hr	13940m <sup>3</sup>	2.83m <sup>3</sup> /hr	24782m <sup>3</sup>
110 psi	0.68m <sup>3</sup> /hr	5932 m <sup>3</sup>	1.52m <sup>3</sup> /hr	13347m <sup>3</sup>	2.71m <sup>3</sup> /hr	23727m <sup>3</sup>
100 psi	0.65m <sup>3</sup> /hr	5656 m <sup>3</sup>	1.45m <sup>3</sup> /hr	12725m <sup>3</sup>	2.58m <sup>3</sup> /hr	22623m <sup>3</sup>
90 psi	0.61m <sup>3</sup> /hr	5362 m <sup>3</sup>	1.37m <sup>3</sup> /hr	12072m <sup>3</sup>	2.45m <sup>3</sup> /hr	21462m <sup>3</sup>
80 psi	0.58m <sup>3</sup> /hr	5059 m <sup>3</sup>	1.30m <sup>3</sup> /hr	11382m <sup>3</sup>	2.31m <sup>3</sup> /hr	20235m <sup>3</sup>
70 psi	0.54m <sup>3</sup> /hr	4732 m <sup>3</sup>	1.22m <sup>3</sup> /hr	10647m <sup>3</sup>	2.16m <sup>3</sup> /hr	18928m <sup>3</sup>
60 psi	0.50m <sup>3</sup> /hr	4381 m <sup>3</sup>	1.13m <sup>3</sup> /hr	9857 m <sup>3</sup>	2.00m <sup>3</sup> /hr	17524m <sup>3</sup>
50 psi	0.46m <sup>3</sup> /hr	3999 m <sup>3</sup>	1.03m <sup>3</sup> /hr	8998 m <sup>3</sup>	1.83m <sup>3</sup> /hr	15997m <sup>3</sup>
40 psi	0.41m <sup>3</sup> /hr	3577 m <sup>3</sup>	0.92m <sup>3</sup> /hr	8048 m <sup>3</sup>	1.63m <sup>3</sup> /hr	14308m <sup>3</sup>

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Pressure Management - Savings

## Example of Potential Savings

- Assume 6 – 3mm leaks
- 8 hour reduction period

Case 1 - Pressure Reduction - 100 psi to 80psi

- Annual Volume of Water Saved = 1200 m<sup>3</sup>

Case 2 - Pressure Reduction - 80 psi to 60psi

- Annual Volume of Water Saved = 1350 m<sup>3</sup>

ST. JOHN'S

DEPARTMENT OF PUBLIC WORKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION

# Leak Detection

## Future Plans for CSJ

- Continue to Install Zone Water Meters
- Implement Remote Data Collection
- Calculate Minimum Night Flow for each zone
- Conduct Pilot project for Pressure management
- Investigate feasibility of extending leak detection to 12 month operation.



A panoramic view of St. John's, Newfoundland, at night. The city lights are reflected in the harbor water. The sky is a deep blue, and the city lights are a mix of warm yellow and cool white. The harbor is filled with ships and buildings, and the city extends up a hillside in the background.

# Thank You

ST. JOHN'S

DEPARTMENT OF PUBLIC PARKS AND PARKS  
ENVIRONMENTAL SERVICES DIVISION