



GRANULAR-AGGREGATE RESOURCES OF NTS MAP AREA 13B/16

MAP 2011-19

LEGEND

Sample types (based on laboratory sieve analysis - see Table 1)

- Sample Symbol** **Definition**
- Commonly gravel or sand, having silt-clay content < 5 percent. Deposits are commonly graded and stratified
- ▲ Commonly till, poorly graded and of variable grain size, having a silt-clay content (> 5 and ≤ 15 percent) and stone size exceeding allowable limits for most geotechnical purposes (except subgrade uses) without processing (i.e., washing, screening or crushing)
- + Commonly silty till, silt or clay samples, having silt-clay content > 15 percent

Multiple samples taken from the same site in different years are listed in order from oldest to youngest. Multiple samples taken at the same site in the same year are listed in order, from the top of the exposure to the bottom.

Note
This is a composite legend for all granular-aggregate resource maps. All aggregate zones, study areas, and sample types shown in the legend may not appear on this map. Aggregate zone classification is based on airphoto interpretation, field investigation and sieve analysis. Areas outside the coloured zones have no known potential for granular materials; however silty tills, rock rubble suitable for fill, and bedrock suitable for aggregate may be present. Classification criteria used on this map do not consider current or conflicting land uses, nor do they guarantee either access to, or the quality of, the material located within these zones.

ZONES OF AGGREGATE POTENTIAL

- Contains granular materials; probability of locating economic deposits is moderate to high
- Contains thin (less than 2 m) or discontinuous granular materials; also includes areas where extent of thicker deposits could not be determined by field investigation; probability of locating economic deposits is moderate to low
- May contain granular materials but deposits are not substantiated by field investigation; probability of locating economic deposits is moderate to low
- Material of granular composition (e.g., sandy tills and colluvium) that generally contains up to 8 percent silt-clay, but could be improved for higher grade uses by washing or screening
- Contains sand-size granular materials; high potential for economic exploitation of sand; low to moderate potential for coarser granular materials
- Eskers: sinuous ridges of granular materials; moderate to high potential for economic exploitation
- /// Till ridge 5-20 m high and 100-3000 m long; perpendicular to ice flow
- Till and bedrock ridge 1-50 m high and 10-3000 m long; parallel to ice flow
- Study area within the dashed outline

In addition to this map data, a granular-aggregate database is accessible in the Geoscience Atlas of Newfoundland and Labrador (<http://gis.gov.nl.ca/gis/geoscience/>) for all granular-aggregate maps and sample data. The database provides information on more than 13 000 samples collected from 230, 1:50 000-scale map areas in Newfoundland and Labrador.

This map was produced from airphoto interpretation and field work conducted in 2010 (Ricketts, 2011).

GIS / digital cartography by T. Paltanavage.

The location of roads added to topographic map base are approximate.

Elevation in metres above mean sea level. Contour interval 10 metres.

Copies of this map may be obtained from the Geoscience Publications and Information Section, Geological Survey, Department of Natural Resources, Government of Newfoundland and Labrador, P.O. Box 8700, St. John's, NL, Canada, A1B 4J6.

This map is subject to review and revision. Comments to the author concerning errors or omissions are invited.

Base from maps published by Surveys and Mapping Branch, Department of Natural Resources, Ottawa, Canada.

OPEN FILE 13B/16/0036

PUBLISHED 2011

Department: <http://www.nr.gov.nl.ca/nr/>

Geological Survey: <http://www.nr.gov.nl.ca/nr/mines/geoscience/>

E-mail: pub@gnr.ca

References

Kirby, F.T., Ricketts, R.J., and Vanderveer, D.G.
1983: Inventory of aggregate resources in Newfoundland and Labrador: information report and index maps. Newfoundland Department of Mines and Energy, Mineral Development Division, Report 83-2, 36 pages.

Ricketts, M.J.

2011: Granular-aggregate mapping along the Trans Labrador Highway from Conwright Junction to the Churchill River. In Current Research, Geological Survey, Department of Natural Resources, Government of Newfoundland and Labrador, pages 69-88.

Recommended citation

Ricketts, M.J.
2011: Granular-aggregate resources of NTS map area 13B/16. Geological Survey, Department of Natural Resources, Government of Newfoundland and Labrador, Map 2011-19, Open File 13B/16/0036.

Note

Open file reports and maps issued by the Geological Survey Division of the Newfoundland and Labrador Department of Natural Resources are made available for public use without being formally edited or peer reviewed. They are based upon preliminary data and evaluation. The purchaser agrees not to provide a digital reproduction or copy of this product to a third party. Derivative products should acknowledge the source of the data.

Disclaimer

The Geological Survey, a division of the Department of Natural Resources (the "authors and publishers"), retains the sole right to the original data and information found in any product produced. The authors and publishers assume no legal liability or responsibility for any alterations, changes or misrepresentations made by third parties with respect to these products or the original data. Furthermore, the Geological Survey assumes no liability with respect to digital reproductions or copies of original products or for derivative products made by third parties. Please consult with the Geological Survey in order to ensure originality and correctness of data and/or products.

GRAIN-SIZE ANALYSES

Grain-size results from the 63, 32, 16 and 8 mm mesh sieves were obtained at the sample site location by sieving approximately 15 kg of material. A 500 to 1000 gm soil of the <8 mm material (sand-silt-clay) was retained for laboratory sieve analysis. Laboratory sieve analysis included the use of seven sieves with mesh openings of 4, 2, 1, 0.5, 0.25, 0.125, 0.062 and the -0.062 mm pan fraction. Samples were wet and/or dry sieved (Korby et al., 1983) depending on silt-clay content and consistence of particles.

Table 1: Exposure thickness (Exp), estimated deposit thickness (Dep), petrographic number (PN), grain-size percentages (based on percent retained on the 63 mm down to the -0.062 mm mesh sieves) and gravel (Grv), sand and silt-clay (SL-CL) content of sample material collected in NTS area 13B/16.

Sample	Exp	Dep	PN	Percent retained through sieve opening (millimetres)										Grv	Sand	SL-CL		
				63	32	16	8	4	2	1	0.5	0.25	0.125				0.062	
103081	1.0	2.0	142	4.8	13.4	9.8	14.3	6.3	13.1	11.7	8.6	6.8	4.8	2.8	3.7	46.9	48.7	4.4
103082	1.8	113	12.2	3.2	1.3	2.0	0.7	3.3	7.8	10.4	16.8	17.3	11.8	13.3	19.1	64.6	16.3	
103083	3.0	176	18.8	4.7	6.5	10.5	6.1	5.7	5.1	5.7	8.6	9.0	6.8	12.6	45.1	40.7	14.2	
103084	4.0	4.0	185	24.9	15.3	10.5	7.9	6.7	10.7	9.4	5.2	4.4	2.6	1.6	0.7	63.7	35.2	1.1
103085	2.0	2.0	124	7.6	3.1	9.6	14.2	12.1	21.2	15.9	10.7	3.3	1.1	0.7	0.5	43.6	55.8	0.7
103089	5.0	5.0	151	4.7	14.0	7.9	8.1	6.8	14.1	22.5	16.9	3.3	0.8	0.5	0.3	39.9	59.7	0.4
103090	7.0			3.2	7.1	19.5	31.6	25.8	10.7	1.5	0.4	0.3	8.5	91.1	0.4			
103091	10.0			0.0	0.0	0.6	2.5	9.5	28.3	40.4	16.2	3.5	0.0	92.7	7.3			
103092	10.0	3.0	165	15.1	10.8	10.4	11.0	12.0	15.4	13.6	7.7	2.4	0.8	0.4	0.4	56.3	43.2	0.5
103093	10.0	7.0		0.0	2.0	5.5	19.1	30.7	26.7	11.6	3.3	1.3	1.5	96.4	2.1			
103094	10.0	10.0		0.0	0.0	0.1	0.6	7.7	35.0	34.2	17.3	5.1	0.0	90.6	9.4			
103095	10.0	129	13.3	18.0	8.1	6.9	7.8	13.6	16.2	8.8	3.9	1.6	1.1	0.8	52.1	46.8	1.1	
103096	9.0	3.0	151	18.6	13.4	9.9	7.2	5.0	9.0	14.6	12.3	6.0	2.2	1.0	0.7	52.9	46.1	0.9
103097	9.0	6.0		1.9	6.0	7.3	19.5	37.8	21.5	4.8	0.9	0.4	6.4	93.0	0.6			
103098	8.0	8.0	173	41.8	18.2	6.7	5.5	5.6	8.0	6.7	3.7	1.8	0.8	0.7	0.3	76.5	23.1	0.5
103099	10.0	3.0	118	18.5	14.6	5.9	4.8	5.4	12.6	22.6	11.8	2.7	0.6	0.3	0.2	47.9	51.9	0.2
103100	10.0	7.0		0.0	0.1	4.7	26.5	44.1	17.2	4.4	2.1	0.9	0.1	98.5	1.4			
103101	4.0	4.0	134	7.4	9.5	19.1	15.2	12.9	13.0	13.4	6.0	1.8	0.8	0.5	0.4	60.9	38.5	0.6
103102	3.0	4.0	148	9.0	5.9	7.3	10.7	10.5	17.5	22.4	11.5	3.6	0.9	0.4	0.3	40.7	58.9	0.4
103103	3.0	3.0	186	24.4	11.0	12.1	14.6	11.4	11.9	6.5	3.9	2.3	0.7	0.4	0.8	70.7	28.5	0.9
103108	5.0	5.0	271	12.0	9.4	9.3	8.1	7.8	8.7	9.3	9.2	7.2	3.9	2.9	12.3	44.6	42.4	13.0
103109	6.0	6.0	198	0.0	13.3	13.9	19.7	21.5	16.1	7.1	3.5	2.0	1.2	1.1	0.7	63.0	36.0	1.0
103110	1.0	2.0	245	0.0	3.8	5.5	12.5	2.7	4.8	10.2	10.7	12.8	11.4	9.1	16.5	23.8	57.4	18.8
103111	3.0	3.0	181	9.8	4.7	5.9	5.9	10.5	9.4	7.4	5.9	8.6	8.3	6.4	16.1	34.3	49.0	17.7
103112	7.0	7.0	213	10.9	15.2	10.7	9.1	5.8	6.6	6.3	6.5	8.2	7.5	4.9	8.3	50.2	40.2	9.6
103113	6.0	6.0	144	21.8	7.4	6.4	4.4	5.2	5.5	5.9	6.5	9.0	7.9	7.3	12.7	43.9	41.6	14.6
103114	4.0	4.0	116	23.5	10.5	7.2	5.9	5.8	3.4	3.7	4.7	8.3	11.5	6.5	9.0	51.4	37.9	10.7
103115	2.0	4.0	137	11.0	8.3	6.9	4.9	2.7	4.6	5.8	7.5	10.1	9.7	7.8	20.7	33.0	44.3	22.7
103125	1.4	1.4	173	35.3	18.3	18.9	13.2	9.3	2.8	0.6	0.3	0.3	0.2	0.2	0.5	92.7	6.7	0.5

