



GRANULAR-AGGREGATE RESOURCES OF THE WABUSH LAKE MAP AREA (NTS 23G/02)

MAP 2013-11

LEGEND

Sample types (based on laboratory sieve analysis - see Table 1)

- Sample Symbol Definition**
- Commonly gravel or sand, having silt-clay content < 5 percent. Deposits are commonly graded and stratified
 - ▲ Commonly silt, poorly graded and of variable grain size, having a silt-clay content (> 5 and < 15 percent) and stone size exceeding allowable limits for most geotechnical purposes (except subgrade uses) without processing (i.e., washing, screening or crushing)
 - + Commonly silty silt, silt or clay samples, having silt-clay content > 15 percent
 - × Site observation - no sample collected

Multiple samples taken from the same site in different years are listed in order from oldest to youngest. Multiple samples taken at the same site in the same year are listed in order, from the top of the exposure to bottom.

Note
This is a composite legend for all granular-aggregate resource maps. All aggregate zones, study areas, and sample types shown in the legend may not appear on this map. Aggregate zone classification is based on airphoto interpretation, field investigation and sieve analyses. Areas outside the coloured zones have no known potential for granular materials; however silty tills, rock rubble suitable for fill, and bedrock suitable for aggregate may be present. Classification criteria used on this map do not consider current or conflicting land uses, nor do they guarantee either access to, or the quality of, the material located within these zones.

ZONES OF AGGREGATE POTENTIAL

- Contains granular materials; probability of locating economic deposits is moderate to high
- Contains thin (less than 2 m) or discontinuous granular materials; also includes areas where extent of thicker deposits could not be determined by field investigation; probability of locating economic deposits is moderate to low
- May contain granular materials but deposits are not substantiated by field investigation; probability of locating economic deposits is moderate to low
- Material of granular composition (e.g., sandy tills and colluvium) that generally contains up to 8 percent silt-clay, but could be improved for higher grade uses by washing or screening
- Contains sand-size granular materials; high potential for economic exploitation of sand; low to moderate potential for coarser granular materials
- Eskers; sinuous ridges of granular materials; moderate to high potential for economic exploitation
- Study area within the dashed outline

In addition to this map data, an aggregate database is accessible in the Geoscience Atlas of Newfoundland and Labrador (<http://gis.geosur.gov.nl.ca>) for all granular-aggregate maps and sample data. The database provides information on more than 13 000 samples collected from 230, 1:50 000-scale map areas in Newfoundland and Labrador.

This map was originally produced in a series of basemap maps from airphoto interpretation and field work (Environmental Geology Section, 1983).

The location of roads added to topographic map base are approximate.

Elevation in feet above mean sea level. Contour interval 50 feet.

Digital Cartography by T. Pattanavajana.

Copies of this map may be obtained from the Geoscience Publication and Information Section, Geological Survey, Department of Natural Resources, Government of Newfoundland and Labrador, P.O. Box 8700, St. John's, N.L., Canada, A1B 4J6.

This map is subject to review and revision. Comments to the author concerning errors or omissions are invited.

Base from maps published by Surveys and Mapping Branch, Department of Natural Resources, Ottawa, Canada.

OPEN FILE 023G/02/0295
This map succeeds Map 82-254, Open File LAB/0607

PUBLISHED 2013

Department: <http://www.nr.gov.nl.ca/>
Geological Survey: <http://www.nr.gov.nl.ca/mines/geoscience/>
E-mail: pub@gov.nl.ca

References

- Environmental Geology Section
1983. 1:50 000 scale aggregate resource maps outlining zones of aggregate potential within a 6-km-wide corridor in Labrador. Newfoundland Department of Mines and Energy, Mineral Development Division, Map 82-254, Open File LAB/0607.
- Kirby, F.T., Ricketts, R.J. and Vanderveer, D.G.
1983. Inventory of aggregate resources in Newfoundland and Labrador; information report and index maps. Newfoundland Department of Mines and Energy, Mineral Development Division, Report 83-2, 36 pages.

Recommended citation


Ricketts, M.J.
2013. Granular-aggregate resources of the Wabush Lake map area (NTS 23G/02). Government of Newfoundland and Labrador, Department of Natural Resources, Geological Survey, Map 2013-11, Open File 023G/02/0295.

Note



Open File reports and maps issued by the Geological Survey Division of the Newfoundland and Labrador Department of Natural Resources are made available for public use without being formally edited or peer reviewed. They are based upon preliminary data and evaluation. The purchaser agrees not to provide a digital reproduction or copy of this product to a third party. Derivative products should acknowledge the source of the data.

Disclaimer

The Geological Survey, a division of the Department of Natural Resources (the "authors and publishers"), retains the sole right to the original data and information found in any product produced. The authors and publishers assume no legal liability or responsibility for any alterations, changes or misrepresentations made by third parties with respect to these products or the original data. Furthermore, the Geological Survey assumes no liability with respect to digital reproductions or copies of original products or for derivative products.



MAP 2013-11 WABUSH LAKE NEWFOUNDLAND AND LABRADOR



GRAIN-SIZE ANALYSES

Grain-size results from the 63, 32, 16 and 8 mm mesh sieves were obtained at the sample site location by sieving approximately 15 kg of material. A 500 to 1000 gm split of the <5 mm material (sand-silt-clay) was retained for laboratory sieve analysis. Laboratory sieve analyses included the use of seven sieves with mesh openings of 4, 2, 1, 0.5, 0.25, 0.125, 0.062 and the -0.062 mm pan fraction. Samples were wet and/or dry sieved (Kirby et al., 1983) depending on silt-clay content and consolidation of particles.

Table 1: Exposure thickness (Exp), estimated deposit thickness (Dep), petrographic number (PN), grain-size percentages (based on percent retained on the 63 mm down to the -0.062 mm mesh sieves) and gravel (Grv), sand and silt-clay (SL-CL) content of sample material collected in NTS map area 23G/02.

Sample	Exp	Dep	PN	Percent retained through sieve opening (millimetres)							Percent									
				63	32	16	8	4	2	1	0.5	0.25	0.125	0.062	Grv	SL-CL				
801170	1.2	8.0	716	0.0	0.0	2.6	0.0	3.3	4.7	6.3	9.6	16.1	16.9	22.2	28.1	51.1	63.7	31.2		
801171	0.4	10.0	632	0.0	1.5	4.6	0.0	5.6	4.9	7.2	10.7	15.6	15.9	7.8	23.2	10.3	64.5	25.2		
801172	2.3	8.0	712	0.0	1.5	5.4	8.5	5.8	11.4	18.5	25.4	17.2	4.9	1.0	0.5	19.7	79.6	0.7		
801173	0.4	10.0	635	0.0	0.6	3.8	2.4	3.4	4.8	6.8	10.1	18.8	18.1	9.4	21.7	9.4	65.5	24.0		
801175	1.3	1.3	253	12.0	17.7	32.1	5.6	0.8	1.4	3.8	5.9	10.4	8.3	1.7	0.2	68.0	31.3	0.6		
801176	0.9	4.0	4.0	0.0	0.0	0.0	0.0	0.0	2.8	11.1	35.0	36.6	10.7	2.5	0.4	94.4	5.2	0.0		
801177	1.2	7.0	873	12.2	1.4	5.4	8.1	1.6	4.5	6.5	8.1	9.1	9.0	6.3	27.8	28.3	42.4	29.4		
801178	1.0	4.0	334	0.0	4.6	5.3	14.5	6.2	12.7	13.5	10.6	8.3	5.9	3.1	15.2	29.1	54.9	16.0		
801179	0.8	6.0	502	0.0	2.3	8.4	4.0	8.7	4.8	5.2	6.6	10.2	14.3	10.6	24.9	21.3	51.1	27.6		
801180	0.6	6.0	860	0.0	1.5	2.2	3.3	2.7	5.2	7.4	8.6	14.8	15.0	8.4	30.0	9.0	58.9	32.1		
801236	1.3	20.0	0.0	0.0	0.0	0.0	0.0	0.0	12.6	21.1	26.5	31.6	7.1	0.7	0.2	9.4	90.3	0.2		
801237	0.8	18.0	0.0	0.0	0.0	0.0	0.0	0.0	2.2	4.1	15.5	34.9	40.0	2.6	0.4	0.2	1.7	98.0	0.3	
802159	12.0	30.0	0.0	0.0	0.0	0.0	0.0	0.2	2.2	14.6	36.6	31.6	11.3	2.5	1.1	0.1	98.2	1.7		
802160	4.0	30.0	221	27.8	8.3	9.8	11.3	2.3	3.0	3.5	5.7	8.4	7.1	3.6	9.3	58.8	31.0	10.2		
802161	3.6	3.0	272	11.0	13.1	5.5	0.0	3.0	3.1	3.9	5.3	7.8	9.9	7.6	29.7	31.8	36.5	31.6		
802162	3.0	13.0	360	2.6	3.9	7.1	11.7	2.5	5.5	7.1	8.8	10.8	10.3	6.1	23.7	27.2	47.6	25.3		
802163	5.0	22.0	0.0	0.0	0.0	0.0	0.0	0.0	3.7	1.8	9.3	20.2	31.9	24.9	6.7	1.1	0.5	51.1	94.2	0.7
802164	4.3	12.0	315	5.7	9.3	8.6	10.7	7.9	8.7	13.8	16.7	10.2	5.8	1.5	1.1	40.3	58.2	1.4		
802165	15.0	8.0	0.0	0.0	0.0	0.0	0.0	2.1	2.2	6.1	8.5	8.9	17.9	25.9	15.3	3.7	78.4	16.9		
802166	15.0	8.0	260	0.0	0.0	0.0	0.0	0.0	0.3	0.5	4.7	43.7	37.8	9.6	3.5	0.0	94.1	5.9		
802167	1.0	15.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
802168	0.8	15.0	0.0	0.0	0.0	1.6	0.0	6.1	20.7	44.7	23.0	2.8	0.6	0.5	1.6	97.7	0.7	0.0		
802169	0.7	13.0	423	9.6	1.3	8.3	12.1	19.7	27.1	15.4	4.6	1.0	0.3	0.3	0.3	46.0	53.6	0.4		
802170	1.7	9.0	608	15.7	10.5	5.2	8.2	2.4	4.1	5.0	6.9	8.1	8.8	6.8	18.3	41.4	38.5	20.0		
802171	1.0	10.0	16.9	8.8	5.2	6.6	3.8	5.0	5.5	7.2	9.3	10.3	6.9	14.6	40.4	43.3	15.3			
802172	1.0	10.0	0.0	0.0	0.0	0.0	0.0	5.6	11.4	13.6	21.8	32.7	12.0	1.7	1.2	4.2	94.2	1.6		
802173	10.0	28.0	242	0.0	16.0	5.1	4.4	2.0	3.2	4.7	7.1	9.5	11.1	8.9	28.0	27.0	42.8	30.2		
803649	1.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.5	39.9	60.3	5.8	0.5	0.0	98.1	1.9	0.0		
803650	12.0	15.0	0.0	0.0	0.0	0.0	19.5	21.1	21.0	19.3	11.8	5.3	1.1	0.4	0.4	35.4	64.1	0.5		