

PROPERTY ORONADA MINES LIMITED
PROJECT 152

PAGE 1

LOCATION 0°00' - 500 W BEARING 110° True HOLE NO. 152-8
 LOGGED BY R. M. Patterson ELEVATION _____ DIP -44° FINAL DEPTH 490.0'
 STARTED November 6, 1956 TESTS (CORRECTED)
 FINISHED November 10, 1956
 CASING 2" 0" 250.0' - 10"
 420.0' - 34"
 CORE SIZE REF

FROM	TO	DESCRIPTION
0.0	10.0	Overburden
10.0	45.0	TUFFS: with jasper - bedding at 60° to core.
45.0	119.0	TUFFS: some jasper 51 - 54" ground core 100-119' - possible flow contact - much alteration.
119.0	187.0	ANDESITE: Altered - very weak disseminated pyrite. 139' - 10" jasper stringer. 146' - 8" quartz stringer.
187.0	283.0	TUFFS: Scattered "flocks" of pyrite
283.0	286.0	TUFFS: Altered-with strong pyrite mineralization following 75° bedding.
286.0	290.0	QUARTZ LENS: Very weak pyrite mineralization - some scattered crystals of galena and sphalerite.
290.0	292.0	TUFFS: Mineralized with pyrite
292.0	302.0	TUFFS: Quartz infected - some pyrite mineralization.
302.0	325.0	TUFFS: Altered - numerous quartz and calcite stringers at 60° - 70° to core. 321 - 325' - some pyrite mineralization
325.0	331.5	MINERALIZED MASS: Quartz-massive pyrite stringers. 330' - 2" pyrite stringer 331' - 1' " "
331.5	343.0	TUFFS AND ANDESITE - Intercalated
343.0	411.0	ANDESITE: Altered - some inter-bedded tuff horizons
411.0	444.0	TUFFS: Bedding at 75° to core.

Cont'd next page

HOLE NO. 152-8

PROPERTY CANADA MINES LIMITED
TR-1011 152

PAGE 2

LOCATION _____ BEARING _____ HOLE NO. 152-2

LOGGED BY _____ ELEVATION _____ DIP _____ FINAL DEPTH _____

STARTED _____ TESTS (CORRECTED) _____

FINISHED _____

CASING _____

CORE SIZE _____

FROM	TO	DESCRIPTION
474.0	475.0	TESTS: rich Jasper
		475.0 - 480' quartz rich Jasper zone with stringers of pyrite.
475.0	477.0	TESTS: quartz impregnated with strong pyrite mineralization.
477.0	477.5	TESTS: 477.5' - 480' weak pyrite mineralization
	480.0	END OF HOLE

HOLE NO. 152-2