

Date: _____ Location: 107° N. 50° W. from _____ Bearing: *Mag.* Hole No. *1*
N.E. corner of shaft
 Logged by: _____ Elevation: _____ Dip: 50° Property: Great Gull Lake,
Nfld.

<u>FROM</u>	<u>TO</u>	<u>DESCRIPTION</u>
0.0	18.0	Overburden.
18.0	59.0	Silicified diabase,
59.0	74.0	Pyritically mineralized sheared diabase.
74.0	75.6	Solid pyrite.
75.6	83.0	Sheared diabase, pyritically mineralized.
83.0	87.0	Quartz and pyrite
		pyrite.
91.0	94.0	Diorite porphyrite dike,
94.0	110.0	Sheared diabase, heavily pyritically mineralized.
110.0	111.0	Solid pyrite.
111.0	117.0	Pyrite, pyrrhotite and chalcocite in sheared diabase.
117.0	167.0	Ore.
167.0	181.0	Fine-grained, blocky diorite porphyrite dike, containing a little copper in small veinlets.
181.0	234.0	Ore.
234.0	239.0	White, soft, feldspathic rock with crystals of chalcocite and quartz.
239.0	256.0	

Hole Started: May 1, 1922.

Hole finished: May 21, 1922.

ASSAY RECORD SHEET

Drill Hole No. 1

GULLBRIDGE MINES LIMITED
Badger, Newfoundland

SAMPLE NO.	FROM	TO	LENGTH	% CU	DESCRIPTION
	108.0	113.6	5.6	1.24	Solid pyrite from 110 to 111 feet.
	113.6	118.0	4.4	3.34	Pyrite, pyrrhotite and chalcopyrite in sheared diabase from 111 to 117.
	118.0	122.5	4.5	2.10	
	122.5	126.0	3.5		
	126.0	130.0	4.0	4.03	
	130.0	131.5	1.5		
	131.5	136.5	5.0	1.92	
	136.5	141.5	5.0	2.79	
	141.5	146.5	5.0	2.41	
	146.5	151.5	5.0	3.34	
	151.5	156.5	5.0	3.10	
	156.5	161.5	5.0	4.40	
	161.5	167.0	5.5	3.91	
	181.0	186.0	5.0	4.03	
	186.0	191.0	5.0	4.03	
	191.0	196.0	5.0	3.29	

ASSAY RECORD SHEET

GULLBRIDGE MINES LIMITED
 Padger, Newfoundland

Drill Hole No. 1

Page 2

SAMPLE NO.	FROM	TO	LENGTH	% CU	DESCRIPTION
	196.0	201.0	5.0	2.36	
	201.0	206.0	5.0	3.29	
	206.0	211.0	5.0	2.54	
	211.0	216.0	5.0	1.92	
	216.0	222.0	6.0	2.92	
	222.0	228.0	6.0	3.97	
	228.0	234.0	6.0	3.35	

Summary :

108.0 234.0 126.0 2.69