

FALCONBRIDGE NICKEL MINES LIMITED

Date: June 1, 1951 Location: 12 1/2 00 S Bearing: East 200 W. of O.R.L. Hole No. G.B.39
Logged by: L. Hudson Elevation: _____ Dip: -45° at collar Property: Gull Pond, Nfld.

DIP TESTS:

<u>Footage</u>	<u>Angle etched on tube</u>	<u>Corrected Angle</u>
0.0	Collared at -45°	
150.0	53 1/2 degrees	44 degrees
314.0	45 1/2 "	37 "

<u>FROM</u>	<u>TO</u>	<u>DESCRIPTION</u>	<u>SAMPLE NO.</u>
0.0	10.0	Overburden: Mostly sand with occasional small boulders.	
10.0	81.0	Fine grained to medium grained dark grey-black, dolerite dyke with occasional quartz, carbonate, and epidote fracture-fillings locally slightly magnetic. Core ground as follows: 57.0-59.0, 59.3-61.0, 65.3-66.4.	
81.0	89.0	Fine grained, dark greyish-green, andesite, slight lineation at 50° - 60°.	
89.0	194.5	Very fine grained, light grey, oremulated tuff, with locally injected quartz, sericitisation and minor disseminated pyrite. Core ground 158.3 - 160.0.	
194.5	208.0	Massive sulphides (pyrite) and injected quartz.	
208.0	237.5	Same as 89.0-194.5.	
237.5	260.0	Fine grained to medium grained, grey-blue amygdaloidal andesite.	
260.0	314.0	Fine grained to medium grained, grey-blue rock of dioritic composition.	

END OF HOLE.

A.X.T. Core to 21.0

Hole started June 1, 1951.
Hole finished June 5, 1951.

AXT casing left in & EXT casing left in, hole left open.

Note: tried to pull EXT casing but could not pull it satisfactorily, probably due to cement in hole.

Cemented hole four times, caving ground at 75-100'.

ASSAY RECORD SHEET

Hole No. GB-39

GULLBRIDGE MINES LIMITED
Badger, Newfoundland

SAMPLE NO.	FROM	TO	LENGTH	% CU	CU	DESCRIPTION
2172	89.0	94.7	5.7			Very fine grained, light grey crenulated tuff, with injected quartz and minor pyrite and Zn ₂ S.
2173	94.7	98.7	4.0			Very fine grained, light grey, well crenulated tuff with minor pyrite and Zn ₂ S.
2174	194.5	208.0	13.5	0.10		Massive sulphides (pyrite) and injected quartz.