

GULLBRIDGE MINES LIMITED

Date: Sept. 15, 1952. 400' W. of A base line, along line A.64 Hole No. G.B. 66

Logged by: L. Hudson Bearing: N. 124 E. Dip: 45° Property: Gull Pond, Nfld.

No tests

AXT core 12.0-13.0

0.0 collared at -45°

245.0 - 50° - 43 degrees.

Hole started: August 11th, 1952. Hole finished: August 25th, 1952. Casing pulled.

From	To	Description
0.0	12.0	Overburden: sand and small boulders.
12.0	62.7	Fine-grained, light grey-brown rhyolite, with occasional amygdaloids.
62.7	99.8	Fine-grained, green, altered andesite; fractured and brecciated, with numerous carbonate fracture-fillings. 99.8 contact makes an angle of 50° with the core axis.
99.8	134.2	Fine-grained, light grey-brown rhyolite, with abundant quartz fracture-fillings.
134.2	141.7	Andesite similar to 62.7-99.8, but shows slightly contorted color banding.
141.7	156.0	Fine-grained, light blue-grey rhyolite, with assimilated andesite and carbonate fracture-fillings locally.
156.0	211.0	Fine-grained, blue-black, sheared andesite locally fractured and brecciated, with carbonate fracture-fillings
211.0	252.1	Andesite, similar to 62.7 - 99.8
252.1	254.0	Fine-grained, light blue-grey, sheared tuff.
	254.0	End of hole.