

GULLBRIDGE MINES LIMITED

Date: February 6, 1952. 30/008 & 160' W of 2 "E" base line. Hole No. G.B. 115
 Logged by P. Sonnenfeld Bearing: E. along line. Dip 70° Property: Nfld. Concession
 L.G. Hudson 30-005 0.0 collared @ 70° Gull Pond, Nfld.
 425.0 - 70°- 63° Claims: 3415, 3417
 A.X.T. core 55.5 - 56.5' 3419, 3421

Hole started: January 23, 1952. Hole finished: January 31, 1952. All casing pulled.

From	To	Description
0.0	55.5	Overburden: 50.5' Water and 5.0' Mud.
55.5	76.5	Fine grained black basalt with occasional quartz fracture fillings, some epidote developed. Lower contact 40° with the core axis.
76.5	87.1	Similar to previous, with moderate amount of calcite fracture - fillings at an angle of 25° with the core axis.
87.1	98.2	Fine grained, black basalt, highly brecciated, silicified and reconsolidated, considerable chlorite and epidote developed, mostly in fracture-fillings at 20° to the core axis.
98.2	253.5	Fine grained, black basalt with occasional calcite stringers. 240.8 - 241.2 amygdaloidal horizon
253.5	274.0	Similar to previous, fractured and brecciated with abundant quartz and epidote fracture-fillings.
274.0	425.0	Fine grained to medium grained, black to green andesite, with development of amphibole, increasing with depth; locally fractured with considerable epidote developed.
	425.0	End of hole.