

AIRBORNE GEOPHYSICAL SURVEY OF THE BURIN PENINSULA REGION, NEWFOUNDLAND

**NTS MAP AREAS
1M/06, 1M/07, 1M/10 AND 1M/11**

**VLF-EM TOTAL FIELD
24.0 kHz, 25.2 kHz & 22.1 kHz (Cutler, MN, LaMoure, ND & Skelton, UK)**

**MAP 2022-22
OPEN FILE NFD/3402
Map 22 of 26**

G.J. Kilfoil

ABOUT THE SURVEY

Introduction
This quantitative gamma-ray spectrometric, aeromagnetic and VLF-EM airborne geophysical survey of Burin Peninsula region, Newfoundland, was completed by Sander Geophysics Limited. The survey was flown from November 12th 2021 to March 22nd, 2022 using a single Cessna 208 Caravan (C-GSCV). The nominal traverse and control line spacings were, respectively, 150 m and 1000 m, and the aircraft flew at a nominal terrain clearance of 90 m at an airspeed between 200 and 270 km/h. Traverse lines were oriented 130° with orthogonal control lines. The flight path was recovered following post-flight differential GPS corrections using raw data recorded by Global Positioning Systems in the survey aircraft and a static reference station.

Gamma-ray Spectrometric Data
The airborne gamma-ray measurements were made with a Sander Geophysics SGLSpec gamma-ray spectrometer using fifteen 1024x1024x60 mm NaI (Tl) crystals. The main detector array consisted of twelve crystals (total volume 60 x 4 litres). These crystals total volume 12.8 litres), shielded by the main array, were used to detect variations in background radiation caused by atmospheric radon. The system continuously adjusted the gain of each crystal by monitoring the natural potassium, uranium, and thorium peaks. A small cesium source was used to supplement the responses of the three natural peaks for the upward-looking crystals.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by ⁴⁰K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (²¹⁴Pb for uranium and ²¹⁴Pb for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents. Thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are, respectively, 1370-1570 keV, 1660-1860 keV and 2410-2810 keV.

Gamma-ray spectra were recorded at one-second intervals. Data processing followed standard procedures as described in IAEA, 1991 and IAEA, 2003. During processing, the spectra were energy calibrated, and counts were accumulated in the windows described above. Counts from the radon detectors were recorded in a 1680 - 1860 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for cosmic radiation activity from cosmic radiation radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over the Breckenridge, Quebec calibration range.

Corrected data were interpolated to a 30 m grid interval. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of outcrop, overburden, vegetation cover, soil moisture and surface water. As a result, the measured concentrations are usually lower than the actual bedrock concentrations. The total air absorbed dose rate in milligrays per hour was determined from measured counts, having energies between 400 and 2910 keV.

Magnetic Data
The magnetic field was sampled 10 times per second using three split-beam cesium vapour magnetometers (sensitivity = 0.005 nT) mounted inside the tail boom and two wingtip pods of the aircraft. This array of sensors form a horizontal gradiometer with a lateral dimension of 19.20 m and a longitudinal dimension of 0.95 m. Differences in magnetic values at the intersections of control and traverse lines were computer-analyzed to obtain a mutually leveled set of flight-line magnetic data. The International Geomagnetic Reference Field (IGRF) defined at the average GPS altitude of 240 m for the date January 1st 2022 was then removed. Removal of the IGRF, representing the magnetic field of the Earth's core, yields a residual component related essentially to magnetization within the Earth's crust. An enhanced version of the leveled magnetic data was calculated by leveraging lateral and longitudinal gradients to better define short wavelength signals, which was then resampled to a 30 m grid interval.


The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes long wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of the vertical derivative map is the coincidence of the zero-value contour with vertical contacts of magnetic units at high magnetic latitudes (Hood, 1965).

VLF-EM
Very low frequency (VLF) electro-magnetic data was measured using a Herz Totem 2A VLF-EM receiver mounted in a 2.5 m fibreglass stinger installed on the tail of the aircraft. For this survey, combinations of Line and Ortho data from the VLF stations in Cutler, Maine (24.0 kHz), LaMoure, North Dakota (25.2 kHz) and Skelton, UK (22.1 kHz) provide complete coverage of the survey area for both Total and Quadrature representations of the VLF signal. Variation in signal quality from the different stations is apparent in the data as bands of more or less coherent data.


Additional Information
Data collection and map production were performed by Sander Geophysics Limited, Ottawa, Ontario. Contract and project management was provided by the Newfoundland and Labrador Department of Industry, Energy and Technology. Copies of this map may be obtained from the Geological Survey, Department of Industry, Energy and Technology, Government of Newfoundland and Labrador, PO Box 8700, St. John's, NL, Canada A1B 4X8.

This map is subject to revision and modification. Comments to the author concerning errors or omissions are invited.
Department Website: <https://www.gov.nl.ca/iel/>
Geological Survey website: <https://www.gov.nl.ca/iel/mines/>
E-mail: pub@geov.nl.ca



Reference
Hood, P.J.
1965. Gradient measurements in aeromagnetic surveying. Geophysics, vol. 30, p. 891-902.



PLANIMETRIC SYMBOLS




NATIONAL TOPOGRAPHIC SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX



Topographic contour interval: 30 metres
Digital topographic data provided by Geomatics Canada, Natural Resources Canada

**MAP 2022-22
BURIN PENINSULA
NTS MAP AREAS 1M/06, 1M/07, 1M/10 AND 1M/11**



Recommended Citation
Kilfoil, G.J.
2022. Airborne Geophysical Survey of the Burin Peninsula region, Newfoundland (NTS Map Areas 1M/06, 1M/07, 1M/10 and 1M/11). VLF-EM Total Field - 24.0 kHz, 25.2 kHz & 22.1 kHz (Cutler, MN, LaMoure, ND & Skelton, UK). Geological Survey, Department of Industry, Energy and Technology, Government of Newfoundland and Labrador, Map 2022-22, Open File NFD/3402.

Note
Open File reports and maps issued by the Geological Survey, Division of the Newfoundland and Labrador Department of Industry, Energy and Technology are made available for public use without being formally edited or peer reviewed. They are based upon preliminary data and evaluation. The purchaser agrees not to provide digital reproduction or copy of this product to a third party. Derivative products should acknowledge the source of the data.

Disclaimer
The Geological Survey, a division of the Newfoundland and Labrador Department of Industry, Energy and Technology (the 'authors and publishers'), retains the sole right to the original data and information found in any product produced. The authors and publishers assume no legal liability or responsibility for any inaccuracies, changes or misrepresentations made by third parties with respect to these products or for derivative products made by third parties. Please consult with the Geological Survey to ensure originality and correctness of data and/or products.