

GOVERNMENT OF NEWFOUNDLAND AND LABRADOR Department of Transportation and Works Highway Design Division

# SECTION 460 CONCRETE PLUGS FOR STORM SEWERS

**INDEX** 

460.01 SCOPE

460.02 MATERIALS

460.03 CONSTRUCTION

**460.04 MEASUREMENT FOR PAYMENT** 

460.05 BASIS FOR PAYMENT

#### 460.01 SCOPE

This specification concerns the supply and placing of cast-in-place concrete plugs to block ends of storm sewers.

## 460.02 MATERIALS

Plugs shall consist of concrete having a strength not less than 20 MPa at 28 days.

#### 460.03 CONSTRUCTION

The end of the storm sewer to be sealed with a plug shall be thoroughly cleaned of all dirt and accumulations of debris.

The concrete shall be placed in the end of the sewer to completely block the opening with a thickness of concrete blocking the end not less than 200 mm at its narrowest point.

# **460.04 MEASUREMENT FOR PAYMENT**

Measurement for payment for concrete plugs, shall be by the number of concrete plugs installed.

## **460.05 BASIS OF PAYMENT**

Payment at the contract unit price per plug shall be compensation in full for all labour, materials and equipment use to supply and place a concrete plug in a storm sewer, including any necessary cutting of pipe regardless of size and dewatering.