GOVERNMENT OF NEWFOUNDLAND AND LABRADOR MUNICIPAL WATER, SEWER, AND ROADS SPECIFICATIONS LIST OF REVISIONS, March 2022

Section Number	Section	Revision
General	Throughout	Each part and specification section has been updated to unify formatting, update references of Engineer or Consultant to Owner where applicable, correct typos, remove gendered language, and update urls and department names. Additional changes will be listed in this document.
Title Page		Title updated to Municipal Water, Sewer and Roads Master Construction Specifications
Master Table of Contents		 Added: New section 01000 Project Specific Specification Previously missing 02577 Pavement Crack Cleaning & Filling Renamed: 02233 to Selected Granular Base & Sub-Base Materials
		 02832 to Wildlife Wire Fences Deleted references to Highway Division website and previously removed specification sections 02502, 02503, and 02504.
Introduction		2022 Committee members updated
User's Guide		Added references to the MERX Pricing Sheets and updated the list of Project Documents.
		Replaced 'Latest' with '(Consultant to Insert Applicable Date)' in the statement "These Project Documents Have Been Prepared For Use With And Require Being Read In Conjunction With".
		Revisions to the Supplementary Specifications now referred to as the Project Specific Specification.
Schedule of Quantities and Prices		Changes to match corresponding language in individual specification sections. See attached Schedule of Quantities and Prices with Track Changes. Where these changes were made to the spec section, they will be noted below.
		Deletion of references to the Tender/Bid Form.

MERX Price		Changed to match changes to SoQaP. Updated to
Table		correct issue with MERX system.
Standard	Table of	Added. Previously listed in Master ToC but was
Forms Table of	Contents	missing.
Contents		i neen igi
Standard	Table of	Added. Previously listed in Master ToC but was
Drawings	Contents	missing.
01000	Project	New template section to match requirements and
	Specific	language changes to User's Guide.
	Specification	
01003	Reference	Added: References throughout the Master
	Documents	Construction Specifications to other codes,
		specifications, standards, guides, legislation, etc. are
0.4.005		to the latest version at time of bid solicitation.
01005	General	Replace 19.1 with:
	Instructions	With the exception Parts 14 and 15, no separate or
		direct payment will be made for work as outlined in
		this specification. Parts 14 and 15, if required, will be included as pay items in the Schedule of Quantities
		and Prices either under this specification or 01020 as
		indicated. Costs of all other work specified in this
		section is deemed to be included in the lump sum
		and unit prices quoted in the Schedule of Quantities
		and Prices.
01010	Mobilization &	Replace 2.2 with:
	Demobilization	The unit price for this item, in the Labrador portion of
		the Province, shall not be greater than 10% of the
		initial contract price including this item but not
		including HST. For projects north of Cartwright the
		unit price for this item shall not be greater than 15%
		of the initial contract price including this item but not
		including HST.
01015	Materials &	Change 2.2 to: Pipes, fittings and pre-cast
	Equipment	maintenance holes not incorporated in the work, up
	Delivered to	to quantities specified in the Schedule of Quantities
	Site	and Prices, shall be purchased by the Owner at the
		invoiced price from the supplier plus 10%, or return
		costs shall be paid by the Owner at the rate of 15%
		of the contract unit price plus transportation at cost
		(ie Force Account without mark-ups) to the
		Contractor's closest storage facility. Items that
		cannot be returned to the supplier MUST be noted
		before tender closing to the Owner's Representative
		(with the approximate cost) and the Owner's
		Representative will issue an amendment instructing

		an how no mont is to be made for unused (full)
		on how payment is to be made for unused (full)
01320	Standby	lengths." In 4.1. after 'complete with change order' add: signed
01320	Compensation	by the Regional Engineer
01370	Schedule of	Rename Part 2: Form of Submittal
01370	Values	Rename Fait 2. Form of Submittai
	Values	Replace 4.2 with: Submit applications for payment on
		a monthly basis in accordance with Article A-4 of the
		Agreement, General Conditions of Unit Price
		Contract, Section GC20 - Application for Payment and
		Section GC 21 - Certificates and Payments. These
		monthly progress applications shall consist of one (1)
		type written copy of the Contract Payment Certificate,
		Detail Sheets for Unit Price Contract (if applicable),
		Materials on Site forms, Testing and Re-instatement
		Allowance form, Reinstatement Certificate, Force
		Account Forms, and any other such forms as will be
		required by the Owner. Proposed change orders that
		have not been signed by the Regional Engineer shall not be included for payment until they are approved.
		These monthly certificates shall be signed by the
		Contractor prior to submission for payment.
01400	Quality	Replace Part 1.1 with: The Owner's authorised
	Control and	representative will approve and the Owner shall pay for
	Testing	services of testing laboratory outside of this contract
	Laboratory	except for the following:
	Services	- 1.1.1 through to 1.1.5 to remain the same.
01545	Safety	Delete 1.3.2. Renumber 1.3.3 as 1.3.2.
	Requirements	
01560	Environmental	In 1.3 replace 'Contractor' with 'Owner's
	Requirements	Representative'.
		Add 2.4. The Contractor shall obtain and new for
		Add 3.4: The Contractor shall obtain and pay for burning permits from Authority Having Jurisdiction.
		burning permits from Authonity Having Sunstitution.
		In 11.7 replace 'DFO' with 'Authorities Having
		Jurisdiction'
		Replace 11.17 with: A copy of all permits shall be
		kept on the Work Site for the duration of the
		Contract, and shall be made available upon request
		of an inspector designated to act on behalf of the
		Department or an employee of an Authority Having
		Jurisdiction.

		In 13.2 replace references to 'Department of Service
		NL' with 'Authority Having Jurisdiction'
01500	Droigot Signa	Delete 13.9 through to the end of Part 13 inclusive.
01580	Project Signs & Sign Supports	Change first paragraph to: This specification outlines the requirements for the installation of a project sign in location on or near the site of the work. The location of the sign is to be determined by the Owner and is to be installed in the first week that the Contractor's personnel mobilizes to site prior to any other work being performed. A photo is to be submitted to the Department immediately."
		Change 1.1.3 to: Project sign is to be supplied by the Contractor and to be 1.22 m x 2.44 m (or otherwise approved by the Regional Engineer). It is to be made of Dibond or 13 mm plywood only."
		Delete 2.2
01582	Sign and Signpost Installations	 Delete 2.6.1 and 2.6.2. Renumber 2.6.3 as 2.6.1. Replace 3.7.3 with: On Types A and Types B signposts, the top and bottom lag bolts must be placed 100 mm from the top and bottom edges of the sign board. Refer to appropriate Sign and Signpost Installation drawings as listed in the Standard Drawings Table of Contents. 5.1 with: Payment at the contract price for sign and signpost installation of a particular type shall be compensation in full for all labour, handling, materials and equipment used, assembly and installation, painting, excavating and backfilling of a back for the fact t
		hole for the footing including compaction of the backfill, installing the sign board and the disposal of all surplus material in accordance with this specification, including the ongoing maintenance of signs.
01600	Material and Equipment	Remove Part 1 in front of References and renumber all subsequent parts. i.e. Part 2 Manufacturers' Instructions is now Part 1. Delete last sentence from renumbered Part 1.2.
01610	Force Account	In 1.3 replace 'Board and Lodging' with
	Payment	'Accommodations at a licenced establishment'

01700	Contract	Add 1.0.7 Commissioning Manuala
01700	Contract Close-Out	Add 1.2.7 Commissioning Manuals
01720	Project Record	Add to 2.3 the items 'MI Project Number' and 'Owner'
	Documents	Delete 2.7
		Add to 3.1 the items 'MI project number; and 'Owner'
		In Part 5 replace 'AutoCAD 2012 or higher format' with 'AutoCAD 2012 or earlier format'
Division 2	Table of Contents	Add sections 02547, 02577, and 02832.
02104	Landscaping, Seeding, Sodding & Tree Preservation	Replace 1.5.4 with: Shrub and tree preservation will be measured by the each and as detailed on the contract documents.
02111	Clearing & Grubbing	Delete 1.2.1.6
	Grubbing	Replace 1.2.2 with: Clearing and grubbing isolated trees, to a depth of 150 mm, will be measured by the each and as detailed on the contract documents.
02202	Rock Removal	Add 1.2.3: Rock removal shall be measured and paid in accordance with the applicable rock excavation sections of 02215, 02223, or 02224.
		Replace 3.2 with: No separate or direct payment will be made for work as outlined in this specification. Costs of all work specified is deemed to be included in the lump sum and unit prices quoted in the Schedule of Quantities and Prices.
02224	Roadway Excavation,	Rename 1.1.1 as: Mass Rock Excavation
	Embankment & Compaction	Rename 1.1.2 as: Mass Common Excavation
02233	Selected Granular Base Course	Renamed section: Selected Granular Base & Sub- Base Materials. Replace references to section name throughout.
		Add to References: Government of Newfoundland and Labrador, Department of Transportation and Infrastructure (TI), Highway Design and Construction Division Specifications

		Replace last sentence of 1.1.2 with: 'Owner shall indicate in the tender documents if tickets are required.' Updated 2.1.5.1 and 2.1.6.1 Class A and Class B
		specifications to match Highways specifications book.
02271	Armour Stone Protection	Delete from 2.1.3: weight, or of a
00070	Cabiana	In 3.1.3 replace 'clam a' with clam bucket as'
02272	Gabions	In 2.4.1 replace 'authority' with 'Owner'
02282	Supply & Installation of Guide Rails	Delete last sentence from first paragraph. Reorganize 1.1.3 and 1.1.4 requirements into list form.
		Move header reference to Sloped and Buried Guide Rail End from 1.1.5 to 1.1.4. Delete from 2.1.2: on a drawing or supplementary general condition
02283	Salvage & Reinstallation of Guide Rail	Replace 1.1.1 with: Measurement for payment for the Salvage and Reinstallation of Guide Rail, whether installed on New or Salvaged Posts, shall be the length of the reinstalled guide rail placed within the limits designated by the Owner, measured in metres, rounded to one decimal place, measured end to end along the face of the railing and terminal sections.
02434	Pipe Culverts	In 1.1.1 replace 'type' with 'thickness' In 1.1.2 replace 'for road culverts' with 'for road and driveway culverts' Delete 1.1.3 and renumber subsequent items.
02481	Channel Excavation, Cleaning & Deepening	Rename 'Part 3 - Excavation' as 'Part 3 Execution'
02528	Concrete Walks, Curbs & Gutters	Add 'Concrete' to the end of name '3.1 Grade Preparation'
02547	Asphalt Tack Coat	Add new section replacing a previously removed section of the same name
02252	Hot Mix Asphaltic	Add 2.3: Asphaltic Concrete Base and Surface Course as well as Adjustments will be paid by the tonne.

	Concerta	
	Concrete Pavement	Add 2.4: Asphaltic Concrete Walkways and Ditches will be paid for by the linear meter for the various thicknesses and widths outlined in the Schedule of Quantities and Prices.
02574	Reshaping & Patching Asphalt Pavement	In 1.1.9 replace last sentence with: All other asphalt work (as determined by the Owner) will be paid by the tonne in accordance with Section 02552.
02577	Pavement Crack Cleaning & Filling	Add new section replacing a previously removed section of the same name
02580	Pavement Markings	Add to References: Government of Newfoundland and Labrador, Department of Transportation and Infrastructure (TI), Highway Design and Construction Division Specifications
		In 3.2.8.3 replace 'removing the paint off the private property' with 'removing the paint off the private or public property'
		In 3.2.9.2 replace 'the Owner's Central Laboratory' with 'a laboratory'
02601	Maintenance Holes, Catch Basins & Ditch	Add new 1.1.2.1: 2 m or less. Shift numbering of subsequent items to accommodate.
	Inlets	Add 1.1.2.9: Greater than 6 m but not more than 6.5 m
		Reorganize 1.1.3, 1.1.4, 1.1.5, and 1.1.6 to match SoQaP
02650	Sewage Pumping Station	In 1.1.1 and 1.1.2 replace 'Supplementary Conditions' with 'Project Specific Specification'
		In 2.6.2.2.2 correct an error in displaying the fraction $\frac{1}{2}$.
02702	Sewer Mains	Renumber 1.2.5 through 1.2.12 to align with SoQaP.2021 becomes in 2022.5.6
		.6 .7 .7 .9
		.8 .10 .9 .11
		.10 .12 .11 .5

.12	.8
for a CCTV insp measured in metres centreline of the w	1.2.8 the sentence 'Measurement bection of watermain shall be s on the ground surface along the atermain from the valve pit entry bit exit point or termination of the g.'
	necting to existing sewer stubs will ch such connection.'
sewer mains will	be measured by each such be measured by each such bered previous 1.2.11 as 1.2.12.
services.	o minimize interruptions to existing
.3 Submit schedul	sewage flows during construction. e of expected interruptions to the and adhere to approved schedule.
In 3.7.2 replace "Pr video or photo CCT	ior to TV inspection" with "Prior to ℃ inspection"
and report presenta prior approval is software will be NAS	st paragraph with: Media storage ation shall be cloud based unless granted by the Department. All SSCO import/export certified (refer g for a full list of compatible
storage device (if a 2.0 or higher com envelopes with I information:	second paragraph with: Digital approved) will be a minimum USB apatibility shall be placed inside abels displaying the following 3.8.2.1 through 3.8.2.6 remains

 4 Contractor 2 The report shall include a completed Index Page with the headers: Street Name From M.H. No. To M.H, No. Page No. 3 Whether inspected at the same time or not, the complete report will be presented together, from upstream to downstream maintenance hole. 4 For video inspection results and findings the heading will state: 1 the street name 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen 5 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers) 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 2 The report shall include a completed Index Page with the headers: Street Name From M.H. No. To M.H, No. Page No. 3 Whether inspected at the same time or not, the complete report will be presented together, from upstream to downstream maintenance hole. 4 For video inspection results and findings the heading will state: 1 the street name 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen 6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding civic numbers). 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description.	10 2010
 with the headers: Street Name From M.H. No. To M.H, No. Page No. 3 Whether inspected at the same time or not, the complete report will be presented together, from upstream to downstream maintenance hole. 4 For video inspection results and findings the heading will state: .1 the street name .2 the maintenance hole numbers applicable to this section .3 the reference drawing number .4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 tatement of soil condition in area of inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding civic numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow 6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description.	
 Street Name From M.H. No. To M.H, No. Page No. 3 Whether inspected at the same time or not, the complete report will be presented together, from upstream to downstream maintenance hole. 4 For video inspection results and findings the heading will state: .1 the street name .2 the maintenance hole numbers applicable to this section .3 the reference drawing number .4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers) .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow 6 The date of of sewer flow 6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 3 Whether inspected at the same time or not, the complete report will be presented together, from upstream to downstream maintenance hole. 4 For video inspection results and findings the heading will state: 1 the street name 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen 5 the texp provide in substrated, frozen 6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 complete report will be presented together, from upstream to downstream maintenance hole. .4 For video inspection results and findings the heading will state: .1 the street name .2 the maintenance hole numbers applicable to this section .3 the reference drawing number .4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers). .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .6 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	-
 upstream to downstream maintenance hole. .4 For video inspection results and findings the heading will state: .1 the street name .2 the maintenance hole numbers applicable to this section .3 the reference drawing number .4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding pole numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow 6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration, protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 Á For video inspection results and findings the heading will state: 1 the street name 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow 6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. 	
 heading will state: 1 the street name 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen 6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .1 the street name .2 the maintenance hole numbers applicable to this section .3 the reference drawing number .4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 2 the maintenance hole numbers applicable to this section 3 the reference drawing number 4 prevailing weather on the day of the inspection, eg., dry, wet, saturated, frozen 6 the date of the inspection 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding civic numbers), telephone poles (with corresponding civic numbers), etc. This drawing will denote: 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 	•
 this section .3 the reference drawing number .4 prevailing weather on the day of the inspection .5 statement of soil condition in area of inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding civic numbers), telephone poles (with corresponding civic numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .3 the reference drawing number .4 prevailing weather on the day of the inspection .5 statement of soil condition in area of inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .4 prevailing weather on the day of the inspection .5 statement of soil condition in area of inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .5 statement of soil condition in area of inspection, eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	-
 eg., dry, wet, saturated, frozen .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .6 the date of the inspection .5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	•
 5 The key plan will consist of a small drawing (not to scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 scale) showing the appropriate location of the two maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	•
 maintenance holes in relation to any nearby reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 reference points such as houses (with corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 corresponding civic numbers), telephone poles (with corresponding pole numbers), etc. This drawing will denote: 1 the maintenance hole numbers 2 the horizontal distance between the maintenance holes 3 the direction of sewer flow 6 The report shall include photographs of: 1 pipe joints that display gaps, spread, or offset; 2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; 3 variance of the grade of the pipe section; and 4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 (with corresponding pole numbers), etc. This drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 drawing will denote: .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .1 the maintenance hole numbers .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .2 the horizontal distance between the maintenance holes .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	•
 maintenance holes .3 the direction of sewer flow 6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. 7 All photographs will labelled and have a corresponding labelled description for the photograph. 8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .3 the direction of sewer flow .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .6 The report shall include photographs of: .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .1 pipe joints that display gaps, spread, or offset; .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .2 signs of infiltration; protruding service lines; crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 crushed, broken or cracked pipe; .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .3 variance of the grade of the pipe section; and .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 .4 gravel or debris or other blockages which may impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
 impede flow. .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	•
 .7 All photographs will labelled and have a corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description. 	
corresponding labelled description for the photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description.	•
photograph. .8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description.	
.8 All photographs will be numbered in order. This number will appear beside them and will be the same number referred to in the description.	
number will appear beside them and will be the same number referred to in the description.	.8 All photographs will be numbered in order. This
	number will appear beside them and will be the
.9 The last page of the report will consist of an area	same number referred to in the description.
	.9 The last page of the report will consist of an area
sewer plan to scale, showing the street inspected	sewer plan to scale, showing the street inspected
for the report and applicable maintenance	
numbers.	numbers.

		.10 Typical DEPARTM MUNICIPA STREET N FROM MH REFEREN LENGT DATE: F WEATHER PIPE SEC TYPE:	IENT PRO LITY: IAME: # TO M CE DRA CE DRA H: PIPE SIZE: & CONDITI	JECT NO.: H# WING: ON: PIF	LINE PE MATER	ion Report SECTION IAL: IATERIAL
		SKETC H	LINE LENGT H (M)	PHOTO #	TAPE REFER ENCE (HOUR S,MINU TES)	OBSER VATION S
		Replace 3.8	8.4 with: Di	gital photo	graph files	shall meet
		or exceed a				
		Delete fron units shall engine and	be indepe	endent fro	m the ma	
		Delete 3.8.	21.3			
02704	Sanitary Sewer Outfall Pipe	Vehicle	Compete aric Cham Operation Occupatio	ency Sta iber, and	ndard for Remotely	Operated
		Delete 1.1.	5			
		Add 1.7.6: will be mea			d/or Photo	Inspection
		Add new 3 PHOTO IN .1 Safety			ER VIDEC) AND/OR
		The under are to mee both for the	et all the sa	afety codes	for diving	practices


 including "The Occupational Health & Safety Regulations, 2012, NL" and the Occupational Safety Code for Diving Operations CAN/CSA - 2275.4 & CAN/CSA - 2275.2. All divers and attendants are to be certified by the applicable regulatory body. Diving Contractors are responsible to ensure that all divers, employees and equipment are certified and capable of performing the work described herein. Prior to any diving inspection, the diving Contractor shall provide a safe work operating procedure & execution plan that shall be suitable to the Owner and applicable safety regulations. The safe work & execution plan shall include, but not be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. 	1	
 applicable regulatory body. Diving Contractors are responsible to ensure that all divers, employees and equipment are certified and capable of performing the work described herein. Prior to any diving inspection, the diving Contractor shall provide a safe work operating procedure & execution plan that shall be suitable to the Owner and applicable safety regulations. The safe work & execution plan shall include, but not be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quarity of, if any, fecal chloroforms if deemed necessary. 		Code for Diving Operations CAN/CSA - Z275.4 & CAN/CSA - Z275.2.
 equipment are certified and capable of performing the work described herein. Prior to any diving inspection, the diving Contractor shall provide a safe work operating procedure & execution plan that shall be suitable to the Owner and applicable safety regulations. The safe work & execution plan shall include, but not be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. 		applicable regulatory body. Diving Contractors are
 shall provide a safe work operating procedure & execution plan that shall be suitable to the Owner and applicable safety regulations. The safe work & execution plan shall include, but not be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. 		equipment are certified and capable of performing the
 applicable safety regulations. The safe work & execution plan shall include, but not be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		shall provide a safe work operating procedure &
 be limited to: 1. working around bodies of water; 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		applicable safety regulations.
 2. boating safety and operator shall hold a valid license; 3. all worker(s) travel from shoreline to dive location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		be limited to:
 location; 4. diver and boat positioning/communication plan while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		- 2. boating safety and operator shall hold a valid
 while underwater; 5. worker rescue & emergency response plan, including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		location;
 including a plan to address the primary transport/rescue boat having mechanical issues during underwater operations; 6. notification to the closest hyperbaric chamber facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		while underwater;
 facility to make the facility aware of the dive in the event of an emergency; 7. dive tables; 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		including a plan to address the primary transport/rescue boat having mechanical issues
 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the work; 10. confirmation/certificates that all divers and attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		facility to make the facility aware of the dive in the event of an emergency;
 attendants are certified by the applicable regulatory body; 11. all equipment is calibrated, certified and capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		 8. harbour/river traffic management plan; 9. a dive schedule explaining the scope of the
 capable of performing the work described herein; 12. a water sample confirming the presence and quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing 		attendants are certified by the applicable regulatory body;
quantity of, if any, fecal chloroforms if deemed necessary. Contractor shall also have their job hazard analysis (JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing		capable of performing the work described herein;
(JHA) for the site and specific task(s). The JHA shall be suitable to the Owner, work crew, and conform to all applicable safety regulations prior to commencing		quantity of, if any, fecal chloroforms if deemed
all applicable safety regulations prior to commencing		(JHA) for the site and specific task(s). The JHA shall
		all applicable safety regulations prior to commencing

.2 Inspection In general the diving Contractor shall provide the following: - 1. A colour video monitor and a clear two-way
 radio communication system that will enable the Owner to communicate with the divers during the inspection operation. 2. A narrated colour video inspection of the above mentioned work. Marine growth shall be removed from the sample area and other areas where
problems are suspected, prior to the video being taped at the Owner's discretion. The narration will clearly describe the location that the diver is inspecting. In particular, at locations where ice damage, scour, deterioration, corrosion, cracks,
or any other distress exists in piling, pier caps, connections, concrete decking, or any other component of the structure, the location will be carefully and accurately recorded as the video is taken.
- 3. Colour still photographs are required for all areas showing any signs of distress in the structure, such as ice damage, corrosion, cracks, pile uplift/deterioration, and scour or undermining of the foundations. Photographs shall be numbered and corresponding to the number of
 the defect on the "Defect Map" in section 4. 4. A defect map showing all problem areas shall be provided showing the size, extent and location of the distress.
 5. One electronic and one paper copy of a detailed report pertaining to the inspection will be submitted no later than two (2) weeks after completion of the work to the Owner. Included with the report will be one electronic and one USB drive copy of the narrated color video and photos
of the inspection. This report will contain plans with detailed measurements, tables, color still photographs, a detailed discussion of the condition of the structure and its' components, and any other information deemed necessary by the Owner to produce a clear and concise report
which thoroughly describes the condition of the structure. .3 Diving Report

	1	
		 The report format to be as follows: Cover sheet Index Preliminary data (location of inspection, climate and water conditions) Abstract Personnel Method of inspection Findings Summary Photographs with location plans Drawings/Attachments The Contractor shall submit a draft report for review by the Owner. Once the draft report is accepted by the Owner with no further changes, the report can be finalized and submitted as a final report.
02713	Water Mains	Renumber previous 3.5 as 3.6Replace 1.4.11 with: Concrete for bedding, thrust blocks, encasement of pipes, supports and cut-off walls will be measured in accordance with Section 03300.Add 1.4.12: Joint restraints, combination air release – vacuum relief valves, valve box extensions, and adjustments to existing valve boxes to grade will be measured by the each.To 2.1.4 add header: Polyethylene pressure pipeIn 2.5.1 replace "Provincial Fire Marshall approved" with "FM approved"In 2.5.2 replace "St. John's standards" with "local standards"Replace 3.7.10 with: Test chambers for infiltration and exfiltration in accordance with Section 02601.
02726	Factory Pre- insulated Piping Systems	Replace1.1.5with:Concreteforbedding,encasement of pipes, supports and thrust blocks will be measured in accordance with Section 03300.Replace1.1.6with:Granular bedding and surround material will be measured in cubic metres in accordance with Section 02223.

		Replace 3.4.1 with: Place bedding and surround material as indicated on contract drawings and in accordance with Section 02223.
		Replace 3.5.1 with: Install pipe in accordance with Section 02713, Section 02702, Section 02704, or Section 02724.
02729	Water Wells	Add new 1.2.3 and renumber subsequent items: Supply and install of drive shoes will be measured by the number of each size installed.
		In 2.2.3 replace "12 inch" with "300 mm" and "5 ft" with "1.5 m"
		In 3.8.2 replace "150 feet/second" with "46 m/s"
		In 3.8.4 correct an error in displaying the fractions $\frac{1}{4}$, $\frac{1}{2}$, and $\frac{3}{4}$.
02831	Chain Link Fences & Gates	Add new 1.2 and renumber subsequent items: Supply and install of barb wire and brackets will be measured in metres.
02832	Wildlife Wire Fence	Rename section as: Wildlife Wire Fence
	T ence	Add new section replacing a previously removed section named Farm Wire Fences
03300	Cast-in-place Concrete	Replace 3.8.1 with: Inspection and testing of concrete and concrete materials will be carried out by a Testing Laboratory in accordance with CSA A23.1-14/A23.2- 14 and the Owner's authorized representative will approve and the Owner shall pay for services of testing laboratory outside of this contract.
03306	Underwater Concreting	Add 1.2.3: Underwater Video and/or Photo Inspection will be measured by lump sum
		Add 3.7 and renumber previous 3.7 as 3.8: 3.7 UNDERWATER VIDEO AND/OR PHOTO INSPECTION .1 Underwater video and/or photo inspection as per Section 02704
Dwg 04060	Concrete Headwall for Sewer or Culvert Pipe	Change note 1 to: Class of Concrete Class: 25 MPa
Dwg 04100	Concrete Sidewalk	Removed reference to Dwg 04150

Dwg 04130 Dwg 04560	Concrete Sidewalk Adjacent to Curb and Cutter Hydrant Connection	Removed reference to Dwg 04150 Change note 2 to: Concrete shall be 25 MPa
Dwg 04600	Watermain Thrust Blocks B	Change note 1 to: Concrete for Thrust Blocks to be 25 MPa
Dwg 04650	Typical Cross Section - Municipal Road	New Drawing. Asphalt thickness – 60mm: Class A – 100 mm; Class B (if required) – 150 mm
Forms	General	All forms were updated for consistency, formatting, Department and Division name, minor updates to match other documents, and for ease of making fillable pdfs.
Form 7	Testing and Reinstatement Allowance	Added references to the specification sections in the table for Testing Allowance
Form 15	Contract Payment	Added MI Project Number, Contractor Invoice #, and *contractor's invoice must be attached to headers. Altered cells for Change Order values and added a place for Revised Subtotal (Not Including HST). Added locations for: Date of Substantial, question on Holdback release. Reorganized calculation table to include location for Reinstatement Allowance and Deficiencies (x2) value.





PAGE NO. : Page 1 of 10 Revision Date: DATE 2021

The quantities set out in this schedule are estimated quantities only and are not to be taken as final quantities by the Contractor. The unit prices bid shall include all labour, plant, materials, overhead, duties, and profit and all other obligations and liabilities under the contract. Do not include taxes in unit or lump sum prices, taxes due are to be added on the last page of this schedule as indicated on the bottom. Totals shall be determined by multiplying the quantity by the tendered unit price.

SECTION	DESCRIPTION	<u>UNIT</u>	<u>QUANTITY</u>	UNIT PRICE	<u>TOTAL</u>
DIVISION #1				5	0.
	<u>Maintain Existing Piped Services</u> xisting Water System <u>(Part 14.2)</u> xisting Sewer System <u>(Part 15.1)</u>	L.S. L.S.	Unit Unit	<u> </u>	Ş
Labrador, or 1	<u>Mobilization & Demobilization</u> aan 5% if on the Island, or 10% if in 5% north of Cartwright, of <u>Sub-Total item a</u> sub total" on last page)	L.S.	Unit	Č.	
 Contribution Supply of a Supply of a Supply of a Overhaul Other (Spectrum) Fuel Adjust Liquid Ast Petroleum 		Allowa Allowa Allowa Allowa Allowa M ³ km Allowa Allowa	ince ince ince ince ince ince ince		
<u>01500</u> 1. Consultan	<u>Temporary Facilities</u> t Site Office	L.S.	Unit		
01560 1. Silt Fence	Environmental Requirements	m			
01570 1. Flag perso 2. Traffic Col	-	Hour L.S.	Unit		

PAGE NO. : Povision Dat	Page 2 of 10 te: DATE 2021	SCHE	DULE OF QU	JANTITIES AN	ID PRICES
SECTION	DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
<u>01580</u>	Projects Signs & Signposts & Installation				
1. Project Sig	n (drawing 04010)	L.S.	Unit		
<u>01582</u>	Sign and Signpost Installations				
1. Type A - X	(specify sign)	Each			
Type B - X	(specify sign)	Each			
Type C - L	/W (specify sign)	Each			
Type D - L	/W (specify sign)	Each			
2. Other Sign	S	Each	- 0		
01710	Reinstatement and Cleaning		J) 、	
1. Fencing	g	m			
2. Ditching		m			
0	Relocate and/or				
Reinstall C		m			
4. Other Strue	ctures (specify)	Speci	fv		
5. Manual Se		m ²			
	Cover for Seed Protection	m ²	-		
• •	Seeding & Mulching	m²			
8. Terraseedi		m²			
9. Supply & F	J	m²			
• • •	Placing Agricultural Limestone	m²			
	pplication of Fertilizer	m ²			
	Placement of Sod	m ²			
SECTION DIVISION #2	DESCRIPTION	UNIT	<u>QUANTITY</u>	UNIT PRICE	TOTAL
02070	Sitework, Demolition & Removal of Structu	ires			
	f Concrete Base	m²			
2. Removal o	f Concrete Pavement	m²			
3. Removal o	f Asphalt Covered Concrete				
Pavement		m²			
4. Removal o	f Concrete Sidewalk	<u>m²</u>			
	al of Curb & Gutter	m			
	al of Catch Basins, Main <u>tenance Hh</u> oles &				
Ditch Inlets		Each			
	al of Fences	m			
	al of Guide Rails	m			
	al of Sanitary Sewers	m			
	Government of Newfour	ndland	and Labrado)r	

PAGE NO. : Page 3 of 10 Revision Date: DATE 2021	SCHE	DULE OF QU	JANTITIES AN	ND PRICES
SECTION DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
 9.10. Removal of Water Lines 10.11. Removal of Culverts 11.12. Removal of Storm Sewers 12.13. Removal of Bridges 13.14. Removal of Mass Concrete 14.15. Removal of Asbestos Cement Pipe 15.16. Removal of Other Items 	m m Each m ³ m Speci	 fy		
02104Landscaping, Seeding, Sodding & Tree Pr1. Manual Seeding2. Temporary Cover for Seed Protection3. Hydraulic Seeding & Mulching4. Terraseeding5. Supply & Placing Topsoil6. Supply & Placing Agricultural Limestone7. Supply & Application of Fertilizer8. Supply & Placement of Sods9. Shrub & Tree Preservation	reservati m ² m ² m ² m ² m ² m ² m ² m ²			
02111Clearing & Grubbing1. Clearing2. Grubbing3. Clearing and Grubbing4. Close Cut Clearing5. Underbrush Clearing and Grubbing6. Isolated Trees Clearing and Grubbing	ha ha ha ha Each			
02215Site Work & Site Grading1. Mass Rock Excavation2. Mass Common Excavation3. Imported Mass Common Backfill4. Supply, Placing & Spreading Topsoil	m ³ m ³ m ³ m ²			
02223Excavation, Trenching & Backfilling1. Main Trench Excavation1. Rock2. Common2. Service Trench Excavation1. Rock2. Common3. Imported Common Backfill	m ³ m ³ m ³ m ³ m ³			

PAGE NO. : Page 4 of 10 Revision Date: DATE 2021	SCHEI	DULE OF Q	UANTITIES AI	ND PRICES
SECTION DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
3.4. Sheeting & Bracing Left in Place		m²		
4.5. Granular Pipe Bedding				
1. Type 1	m³			
2. Type 2	m ³			
3. Type 3	m ³			
3.1 Type 3 Imported	m3			
5.6. Rock Under- <u>Bb</u> edding	m ³		6	
6.7. Trucking, Handling, Stockpiling, Filling, and				
Conditioning, and Reuse of <u>Wet</u> Common Material	m ³			
7.8. Supply & Placement of Marking Tape				
1. Plastic Tape	m			
2. Metallic Tape	m			
02224 Roadway Excavation, Embankment & Co	ompaction		X	
1. Mass Excavation & Backfill				
1. Rock	m ³	, ,		
2. Common	m ³	-		
2. Imported Backfill	••••	/		
1. Rock	m ³			
	m ³	\mathbf{X}		
2. Common				
3. Placing & Spreading Topsoil	m²			
02231 Scarifying & Reshaping				
1. Scarifying & Reshaping incl. Compaction	m ²			
02232 Reshaping Only (up to 100 mm)				
02232Reshaping Only (up to 100 mm)1. Reshaping up to 100 mm incl. Compaction	m²			
1. Reshaping op to too him incl. compactor	111			
02233 Selected Granular Base & Sub Base Mat	erials			
1. Class "A" Granular Base	m ³			
2. Class "B" Granular Sub-Base	m ³			
02250 Calcium Chloride				
1. Calcium Chloride	tonne			
	tonno			
02270 Rip-Rap Protection				
1. Rip-Rap Hand Laid Dry Wall	m ³			
2. Rip-Rap Hand Laid with Sod	m ³			
3. Rip-Rap Grouted	m ³			
	m ³			
4. Rip-Rap Random	IIIř			

PAGE NO. : Page 5 of 10 Revision Date: DATE 2021	SCHE	DULE OF QI	JANTITIES AN	
SECTION DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
02271Armour Stone Protection1. Supply & Placement of Armour Stone (size X)2. Supply & Placement of Armour Stone (size Y)1.3. Supply & Placement of Armour Stone (size Z)	t or m m ³ m ³	3		
02272 <u>Gabions</u> 1. Supply & Placement of Gabions incl. Fill by Hand <u>(wire type)</u>	m ³	_	5	6
02282Supply & Installation of Guide Rail1. Standard Type Guide Rail2. Guide Rail with Additional Posts3. Type "A" Guide Rail4. Type "B" Guide Rail5. Sloped & Buried Guide Rail Section	m m m Each	Ð		
02283Salvage & Reinstallation of Guide Rail1. Salvage & Reinstallation of Guide Rail1. On New Posts2. On Salvaged Posts	m m	× ?		
02284Handrail02410Sub-Drains1. Supply & Placement of Bending Gravel2. Supply & Placement of Granular Filter Material3. Supply & Placement of Sub-Drains (size)02434Pipe Culverts	m m ³ m			
 Supply & Placement of Pipe Culvert (size) (thickness) (type) Supply & Placement of Cut-off Collars Supply & Placement Prefab. End Sections Supply & Placement of Debris Racks Supply & Placement of Concrete Head Walls 	m Each Each Each m ³			
02481 Channel Excavation, Cleaning & Deepening 1. Channel Excavation 1. Rock 2. Common 2. Cleaning & Deepening of Existing Channels	ng m ³ m ³ m			

PAGE NO. : Page 6 of 10 Revision Date: DATE 2021	SCHE	DULE OF QL	JANTITIES AN	ID PRICES
SECTION DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
02496 <u>Timber Crib work</u> 1. Timber Cribwork	m³			
02528Concrete Walk, Curb & Gutters1. Supply & Place Granular Base Material2. Concrete Walks	m³			
(width) (thickness) 3. Combined Curb & Sidewalk (width) (thickness)	m m		5	
 Driveway Ramps With Curb, (width) (thickness) Without Curb, (width) (thickness) 	m m	The second secon	_	5
 Curb & Gutter Curb 	m m	Y)	×	
02547Asphalt Tack Coat1. Supply & Placement of Asphalt Tack Coat	m ²			
02552Hot Mix Asphalt Concrete Paving1. Asphaltic Concrete1. Base Course2. Surface Course3. Asphaltic Concrete Adjustment2. Asphaltic Concrete Walkways	tonne: tonne: tonne:	s		
 (thickness) (width) Asphaltic Concrete Ditch (thickness) (width) 	m ² m			
02574Reshaping & Patching Asphalt Pavement1. Removal of Asphalt Pavement2. Patching of Asphalt Pavement3. Removal and Replacement of Asphalt Pavement	m² m²			
(For Road Projects only)4. Temporary Patching of Asphalt Pavement5. Cutting of Asphalt Pavement	m² m² m			
02575 Cold Planing	m²			
02576 Pulverizing	m²			
02577 Pavement Crack Cleaning & Filling	m			

	: Page 7 of 10 _ ate: DATE 2021	SCHE	DULE OF QI	JANTITIES AN	ID PRICES
ECTION	DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
2580	Pavement Marking				
. Pavemen		L.S.	Unit		
2601	Manholes Maintenance holes, Catch	hasins Ditch	Inlets & Valve	Chambers	
	Placement of Pre-Cast Maintenance I			Onambers	
1. 2 m o		Each			
2. > 2 m	to 2.5 m	Each			
3. > 2.5		Each			
	to 3.5 m	Each			
	m to 4.0 m	Each	-0		
	m to 4.5 m	Each			
	m to 5.0 m	Each			
	m to 5.5 m (etc.) with Safety Landing	Each		_	
	m to 6.5 m with Safety Landing (etc.)	Each			
-	Placement of <u>Maintenance Hole</u> Inflow			X	
Prote		Each			
Outfall St		Each	·		
	n <u>tenance H</u> holes	Each			
	Maintenance Hholes	Each			
Catch Ba		Each			
-	Place Maintenance Hholes	Each	\mathbf{X}		
	ent of Maintenance Hhole/Catch Basin				
-	ent of Maintenance Hhole Cevers	Each			
	Existing Maintenance Hole/Catch	Edul			
•			•		
	Tops	Each			
. Salety La	Indings for Deep Manheles	Each			
650	Sewage Pumping Stations				
	Station_identifier), (Station size), (Pur		ab Unit		
	KW.) <u>, see contract documents & Impe</u> ly and Commission Portable Diesel	ller) <u>L.S</u> Ea	i ch <u>Unit</u>		
			Linit		
Generato		<u>L.S</u> Each	<u>Unit</u>		
702	Pipe Sewer Construction				
	Placement of Sanitary Sewer				
-	ain Line				
I. IVI		m			
2. Š	(size) (type) (thickness) (insulation)	m			
		~			
1. 2.	(size) (type) (thickness)(insulation)	m Each			
	long radius bends	Each			
Supply &	Placement of Storm Sewer				

overnment of Newfoundland and Labrador
Municipal Water, Sewer and Roads
Master Construction Specifications

evision Date: DATE 2021				
(size) (type) (thickness)	m			
ECTION DESCRIPTION	UNIT	QUANTITY	UNIT PRICE	TOTAL
Supply & Install Tees c/w Bends	Each			
Supply & Installation of End Caps	Each			
Supply & Installation of Plugs	Each			
CCT-V- Camera Inspection Services	m			
 Break Into & Connect to Existing				
-Ma <u>intenance H</u> holes	Each			
8. Locate and Connect to Existing Sewer Mains	Each			
9. Locate and Connect to Existing Sewer Stubs	Each		7	
2704 Sanitary Sewer Outfall Pipe				
Outfall Sewer pipe (Ssize) (type) (thickness)	m			
Concrete for Bedding and , Encasement Pipes	m ³			
Other bedding (specify)	m ³			
Tees, Caps, Plugs, Other Fittings_Concrete Head Bl		des. Supports	T	
(Specify)	Each	, 11		
Underwater Video and/or Photo Inspection		a ch Unit		
2710 Foundation & Under Slab Drainage				
Supply & Installation Foundation & Under				
Supply & Installation Foundation & Under Slab Drainage	L.S.	Unit		
Supply & Installation Foundation & Under Slab Drainage	L.S.	Unit		
Slab Drainage	L.S.	Unit		
Slab Drain <u>age</u> 2713 Water Mains	L.S.	Unit		
Slab Drain <u>age</u> 2713 <u>Water Mains</u> Supply & Installation of Water Main	L.S.	Unit		
Slab Drain <u>age</u> 2713 <u>Water Mains</u> Supply & Installation of Water Main (type) (class) (size) (insulation)	0	Unit		
Slab Drain <u>age</u> <u>2713</u> <u>Water Mains</u> Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service <u>Connections</u> Pipe to	0	Unit		
Slab Drain <u>age</u> 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m	0	Unit		
Slab Drain <u>age</u> <u>2713</u> <u>Water Mains</u> Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service <u>connections</u> Pipe to (type) (class) (size) (insulation) m Supply & Install of Fire Hydrants (depth)	ROW	Unit		
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Install of Fire Hydrants (depth) (insulation) m	ROW	Unit		
Slab Drain <u>age</u> 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service Connections Pipe (type) (class) (size) (insulation) m Supply & Installation of Fire Hydrants (depth) (insulation) m Supply & Installation of Fitting (size) (insulation) m	ROW	Unit		
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Fire Hydrants (depth) (insulation) Eac Supply & Installation of Fitting (size) (insulation) 1.	ROW	Unit		
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) M Supply & Install of Fire Hydrants (depth) (insulation) Ead Supply & Installation of Fitting (size) (insulation) 1. Wyes Ead 2. Crosses Ead	ROW		 	
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Im Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Im Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Im Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Im Supply & Installation of Fire Hydrants (depth) Im (insulation) Eac Supply & Installation of Fitting (size) (insulation) Eac 1. Wyes Eac 2. Crosses Eac 3. Reducers Eac	ROW			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) Supply & Install of Fire Hydrants (depth) (insulation) Ead Supply & Installation of Fitting (size) (insulation) 1. Wyes Ead 2. Crosses Ead 3. Reducers Ead 4. End Caps/Plugs Ead	BOW			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) In Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) In Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) In Supply & Installation of Fire Hydrants (depth) Insulation) Eac Supply & Installation of Fitting (size) (insulation) In 1. Wyes Eac 2. Crosses Eac 3. Reducers Eac 4. End Caps/Plugs Eac 5. Bends Eac	ROW			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Fire Hydrants (depth) Eac (insulation) Eac Supply & Installation of Fitting (size) (insulation) Eac 1. Wyes Eac 2. Crosses Eac 3. Reducers Eac 4. End Caps/Plugs Eac 5. Bends Eac 6. Tees Eac	ch			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Fire Hydrants (depth) (insulation) Ead Supply & Installation of Fitting (size) (insulation) 1. Wyes 2. Crosses 3. Reducers 4. End Caps/Plugs 5. Bends 6. Tees 7. Corporation Stops	ROW			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) nr Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) nr Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Service ConnectionsPipe to (type) (class) (size) (insulation) m Supply & Installation of Fire Hydrants (depth) Eac (insulation) Eac Supply & Installation of Fitting (size) (insulation) 1 1. Wyes Eac 2. Crosses Eac 3. Reducers Eac 4. End Caps/Plugs Eac 5. Bends Eac 6. Tees Eac 7. Corporation Stops Eac 8. Saddles Eac	ch			
Slab Drainage 2713 Water Mains Supply & Installation of Water Main (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Service Connections Pipe to (type) (class) (size) (insulation) Supply & Installation of Fire Hydrants (depth) (insulation) Eac Supply & Installation of Fitting (size) (insulation) 1. Wyes 2. Crosses 3. Reducers 4. End Caps/Plugs 5. Bends 6. Tees 7. Corporation Stops	BOW			

PAGE NO. : Page 9 of 10 Revision Date: DATE 2021	SCHEDULE OF QUANTITIES AND PRICES				
(size)	Each				
SECTION DESCRIPTION	Each	UNIT	QUANTITY		TOTAL
6. Supply & Install of Hydrant Extensions (length))				
(insulation) Each		-			
7. Colour Coded Painting of Hydrants	Each		. .		
8. Supply & Install Valves Including Valve Boxes					
(size) (insulation)	Each		·		
9. Supply & Install of Valve Chambers	Each		·	~ —	-
10. Supply & Placement of Concrete Thrust Blocks				\mathbf{G}	- (7.
11.10. Supply & Placement of Joint Restraints (siz	,	Each	$-\mathbf{O}$		
12.11. Supply & Install Combination Air Release -		ו		1	
Relief Valves (size)	Each				
13.12. Supply & Install Valve Box Extensions		Each			
14.13. Adjust Existing Valve Boxes to Grade		Each			
<u>15.14.</u> Swabbing of Water Lines				X	
(size)	m Each		• —		
<u>16.15.</u> Locating & Connecting to Existing System	Each		<u> </u>	-()	
02724 Sewage Force Mains					
1. Supply & Installation of Sewage Force Mains					
(size) (class) (type)(insulation)					
2. Supply & Installation Combination Air					
Release -Vacuum Relief Valve & Chamber	Each				
3. Supply & Installation of Fittings	Laon				
Bends (size) (insulation)	Each				
4. Force Main Connection to Maintenance Holes			- · ·		
4.5. Break into & connect to existing maintenan		eEach			
5.6. Swabbing of Force main (size)		m			
02729 Water Wells					
1. Drilling Unconsolidated Formation	m			_	
2. Drilling in Consolidated Formation	m				
3. Supply & Installation of Casing (type) (size)	m				
4. Supply & Install Drive Shoe	Each				
5. Supply & Installation of Well Screen (size)	L.S.	Unit			
6. Supply & Placement of Gravet Packing	kg.				
7. Supply & Placement of Grouting (40 kg bags)	Each				
8. Well Development	Hour				
9. Disinfection of Well	L.S.	Unit			
10. Test Pumping of Well	Hour		·		
11. Water Quality Testing	L.S.	Unit			
<u>12.</u> Supply & Installation of Well Seals (size)	Each				

Government of Newfoundland and Labrador
Municipal Water, Sewer and Roads
Master Construction Specifications

PAGE NO. : Page 10 of 10 Revision Date: DATE 2021

SCHEDULE OF QUANTITIES AND PRICES

