



NOTES:

1. OUTLET HOLE SIZE 525mm DIAMETER MAXIMUM, LOCATION AS REQUIRED.
2. 200mm DIAMETER KNOCKOUT SHALL ACCOMMODATE SUBDRAIN. KNOCKOUT SHALL BE 60mm DEEP.
3. CENTRE REINFORCING IN BASE SLAB AND WALLS ±20mm.
4. GRANULAR BACKFILL SHALL BE PLACED TO A MINIMUM THICKNESS OF 300mm ALL AROUND THE CATCH BASIN.
5. FRAME, GRATE, AND ADJUSTMENT UNITS SHALL BE INSTALLED ACCORDING TO STANDARD DRAWING 04250.
6. PIPE SUPPORT SHALL BE ACCORDING TO STANDARD DRAWING 04260.
5. ALL DIMENSIONS ARE NOMINAL AND IN MILLIMETERS UNLESS OTHERWISE SHOWN.

ALTERNATE STANDARD HEIGHTS	
ALTERNATE	DIMENSION
A	1980
B	1830

MASTER SPECIFICATIONS

PRECAST CONCRETE TWIN INLET CATCH BASIN
600 x 1450mm

DRAWING NUMBER: 04360

DATE: MARCH 2016

SCALE: N.T.S.