



**NOTES:**

1. OUTLET HOLE SIZE 525mm DIAMETER MAXIMUM, LOCATION AS REQUIRED.
2. 200mm DIAMETER KNOCKOUT SHALL ACCOMMODATE SUBDRAIN. KNOCKOUT SHALL BE 60mm DEEP.
3. GRANULAR BACKFILL SHALL BE PLACED TO A MINIMUM THICKNESS OF 300mm ALL AROUND THE CATCH BASIN.
4. FRAME, GRATE, AND ADJUSTMENT UNITS SHALL BE INSTALLED ACCORDING TO STANDARD DRAWING 04250. STEPS SHALL BE ACCORDING TO STANDARD DRAWING 04280, AND SPECIFICATION SECTION 02601.
5. ALL DIMENSIONS ARE NOMINAL AND IN MILLIMETERS UNLESS OTHERWISE NOTED.
6. CONCRETE TO BE 30 MPa TO MEET CSA A23.1, CLASS C-2 EXPOSURE.

**MUNICIPAL MASTER  
SPECIFICATIONS**

**PRECAST CONCRETE TWIN INLET CATCH BASIN  
600 x 1450mm**

DRAWING NUMBER 04360

DATE: APRIL 2023

SCALE: N.T.S.